

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
Union Texas Petroleum Corporation

3. ADDRESS OF OPERATOR
P. O. Box 808, Farmington, New Mex. 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1770 ft./S; 1660 ft./W lines
AT TOP PROD. INTERVAL: Same as above
AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Spudded and set surface casing <input type="checkbox"/>	

5. LEASE
NM 014023

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
F-27-24-7

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Escrito Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 27, T-24N, R-7W, N.M.P.M.

12. COUNTY OR PARISH | 13. STATE
Rio Arriba | New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6910 R.K.B.

RECEIVED
MAY 11 1983
GEOLOGICAL SURVEY
FARMINGTON, N.M.

RECEIVED
MAY 13 1983
OIL CON. DIV.
DIST. 3

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- Spudded 12-1/4" hole at 4:30 P.M., 5-6-83.
- Drilled 12-1/4" surface hole to a total depth of 300 ft. R.K.B.
- Ran 7 joints 8-5/8", 24.0#, K-55 casing and set at 296 ft. R.K.B.
- Cemented with 236 cu. ft. Class "B" with 3% CaCl₂. Circulated 6 bbls. to surface. Plug down at 12:45 A.M., 5-7-83.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. K. Cooper TITLE Field Oper. Mgr. DATE May 10, 1983

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

MAY 17 1983

NMOCC

FARMINGTON DISTRICT
BY JTC