

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-039-23138

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☒

GAS  
WELL ☐

OTHER

2. Name of Operator

Benson-Montin-Greer Drilling Corp.

3. Address of Operator

4900 College Blvd., Farmington, NM 87402

4. Well Location

Unit Letter I : 1850 Feet From The South Line and 790 Feet From The East Line

Section 21

Township 25 North

Range 2 West

NMPM

Rio Arriba

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

7197' RKB

7. Lease Name or Unit Agreement Name

Janet "A"

8. Well No.

#2

9. Pool name or Wildcat

Gavilan  
Undesignated Gallup

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plug #1 Dakota 7550' - 7735'

Plug #1 A to cover perforated zone from 6657' - 7055' (PBTD 7935', TD 8062')  
Will set retainer above top perforation and squeeze perfs w/ 100 sacks cement  
Will spot 50' cement plug on top of retainer.

Plug #2 to cover Fruitland and Pictured Cliffs formations  
Set cement plug from 3250' - 3470'.

1000'-1700' 2A

Plug #3 to cover surface casing shoe set at 205'  
Set 100' cement plug from 155' - 255'.

Plug #4 surface plug  
Set 50' cement plug from surface to 50' inside 4 1/2" casing.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Albert R. Greer TITLE President

DATE 11-10-97

TYPE OR PRINT NAME Albert R. Greer

TELEPHONE NO. 325-8874

(This space for State Use)

APPROVED BY

Johnny Robinson

DEPUTY OIL & GAS INSPECTOR, DIST. #3

DATE

NOV 12 1997

CONDITIONS OF APPROVAL, IF ANY

As noted above.

NOTIFY AZTEC OGD  
IN TIME TO WITNESS PTA