

(November 1983)
(formerly 9-30)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other In-
structions on
reverse side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

LEASE DESIGNATION AND SERIAL NO.

NM-01139

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Fred Phillips G

9. WELL NO.

1A

10. FIELD AND POOL, OR WILDCAT
Blanco Mesaverde

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

NE/NE Sec10, T25N, R3W

12. COUNTY OR
PARISH

13. STATE

Rio Arriba

N.M.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. TYPE OF WELL: ☒ OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP EN ☐ DEEP BACK ☐ DEEP REPAIR ☐ OTHER

2. NAME OF OPERATOR

Amoco Production Co.

3. ADDRESS OF OPERATOR

501 Airport Drive, Farmington, N M 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 800' FNLx820' FEL

At top prod. interval reported below same

At total depth same

RECEIVED

JUL 12 1985

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

15. DATE SPUDDED 12-10-84 16. DATE T.D. REACHED 1-4-85 17. DATE COMPL. (Ready to prod) 2-26-85 18. ELEVATIONS (OF RKB, RT, GR, ETC.)* 7224'KB 19. ELEV. CASINGHEAD 7210'GR

20. TOTAL DEPTH, MD & TVD 8352' 21. PLUG, BACK T.D., MD & TVD 8302' 22. IF MULTIPLE COMPL., HOW MANY* Two 23. INTERVALS DRILLED BY 0-TD ROTARY TOOLS CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

5866'-5936'- Mesaverde

26. TYPE ELECTRIC AND OTHER LOGS RUN

Dil-SP-GR; EDL-CNL-GR-Caliper

25. WAS DIRECTIONAL SURVEY MADE yes

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9-5/8"	36#, K55	358'	12-1/4"	354 cf class B Ideal	
5-1/2"	17#, K55	8356'	8-3/4"	965 cf class B 50:50	poz. Stage 2
				2206 cf class B 65:	35 poz.

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	8135'	

30. TUBING RECORD

31. PERFORATION RECORD (Interval, size and number)

5866'-5936', 4 jspf, 52" in diameter, for a total of 280 holes

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD) 5866'-5936' AMOUNT AND KIND OF MATERIAL USED 33,000 gals 20# gel and 44,000# 20-40 mesh sand

33.* PRODUCTION

DATE FIRST PRODUCTION 4-20-85 PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing WELL STATUS (Producing or shut-in) Shut-in

DATE OF TEST 6-26-85 HOURS TESTED 3hrs CHOKER SIZE 54/64 PROD'N. FOR TEST PERIOD OIL—RBL. GAS—MCF. WATER—BBL. I GAS-OIL RATIO no flow FLOW. TUBING PRESS. CASING PRESSURE CALCULATED 24 HOUR RATE *0 psig **1150 psig OIL—RBL. GAS—MCF. WATER—BBL. OIL GRAVITY-API (CORR.)

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

Ron Hokit

35. LIST OF ATTACHMENTS

*Rod and pumps in hole ** Shut-in pressures only ACCEPTED FOR RECORD

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED B.D. Shaw TITLE Adm. Supervisor DATE 7-9-85

*(See Instructions and Spaces for Additional Data on Reverse Side)

FAR

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	3030	3305				
Fruitland	3305	3610				
Pictured Cliffs	3610	3890				
Cliffhouse	5360	5485				
Menefee	5485	5840				
Point Lookout	5840	6090				
Gallup	6960	7420				
Dakota	8105	8315				