

CONFIDENTIAL

Form 3160-5
(JUNE 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135

Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT --" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other:

2. Name of Operator

Mallon Oil Company

3. Address and Telephone No.

P.O. Box 3256, Carlsbad, NM 88220 (505) 885-4596

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

860' FSL and 990' FEL (SE SE) Unit P.
Sec. 2, T25N-R2W

5. Lease Designation and Serial No.

NM-40645

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

N/A

8. Well Name and No.

Ribeyowids Fed. 2 No. 16

9. Well API No.

30-039-23554

10. Field and Pool, or Exploratory Area
Mesa Verde, Pictured Cliffs

11. County or Parish, State

Rio Arriba County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐
- Notice of Intent
-
- ☒
- Subsequent Report
-
- ☐
- Final Abandonment Notice

TYPE OF ACTION

- ☐
- Abandonment
-
- ☒
- Recompletion
-
- ☐
- Plugging Back
-
- ☐
- Casing Repair
-
- ☐
- Altering Casing
-
- ☒
- Other: TA Dakota/Mancos
-
- ☐
- Change of Plans
-
- ☐
- New Construction
-
- ☐
- Non-Routine Fracturing
-
- ☐
- Water Shut-Off
-
- ☐
- Conversion to Injection
-
- ☐
- Dispose Water

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this zone.)

Mallon Oil Company set a CIBP at 6707' with 2 sacks cement on top of CIBP, isolating the Mancos 6784'-7618' and the Dakota 7950'-8056'.

Perforate the Mesa Verde 5791'-5799' (16 holes, 8 JSPF). Frac Mesa Verde with 190 bbls gel pad, 40,000 lbs 20/40 sand.

Perforate Pictured Cliffs 3556'-3578' (44 holes, 2 JSPF). Frac Pictured Cliffs with 1500 gls 15% acid, 107 bbls gel pad, 20,000 lbs 20/40 sand. Run 2-3/8" N80 tbg production string.

Initiate Mesa Verde and Pictured Cliffs production.

14. I hereby certify that the foregoing is true and correct

Signed

Theresa A. McAndrews

Title

Office Manager

Date

6/13/97

(THIS SPACE FOR FEDERAL OR STATE OFFICE USE)

Approved By

Title

Chief, Lands and Mineral Resources

Date

JUL 21 1997

Conditions of approval, if any:

Title 18 U. S. C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side