

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

SF 078882

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Canyon Largo Unit

8. FARM OR LEASE NAME

Canyon Largo Unit

9. WELL NO.

356

10. FIELD AND POOL, OR WILDCAT

Devils Fork Gallup

11. SEC. T. R. M., OR BLK. AND

SURVEY OR AREA

Sec. 20, T-25-N, R-06-W
NMMPM

12. COUNTY OR PARISH

San Juan

13. STATE

NM

RECEIVED

14. PERMIT NO.

OCT 15 1985

15. ELEVATIONS (Show whether OF, RT, CR, etc.)

6389' GL

16. BUREAU OF LAND MANAGEMENT Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

FARMINGTON RESOURCE AREA

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PCLL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Running Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-10-85 TD 6140'. Ran 151 jts. 4 1/2", 10.5# K-55 production casing, 6134' set @ 6146'. Float collar set @ 6135'. Stage tools @ 5132' and 2582'. Cemented first stage with 115 sks. Class "B" 65/35 Pozmix, 6% gel and 2% calcium chloride, (186 cu.ft.) followed by 100 sks. Class "B" Poz with 2% gel, 2% calcium chloride and 1/4# fine tuf-plug (124 cu.ft.), 2nd stage with 286 sks. Class "B" 65/35 Pozmix, 6% gel, 2% calcium chloride (463 cu.ft.), 3rd stage with 299 sks. Class "B" 65/35 Pozmix with 6% gel and 2% calcium chloride (485 cu.ft.). WOC 18 hours. Top of cement 1000' T.S.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling Clerk

DATE

10-10-85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

BY