

CONDITIONS OF APPROVAL FOR PERMANENT ABANDONMENT

Operator Conoco Inc. Well Name #76 Lindrith B Unit

1. Plugging operations authorized are subject to the "General Requirements for Permanent Abandonment of Wells on Federal Leases."
2. For wells on Federal leases, Al Yepa with the Cuba Field Office is to be notified at least 24 hours (48 hours if possible) before the plugging operations commence. His phone number is (505) 289-3748. Office hours are 7:45 a.m. to 4:30 p.m.

For wells on Jicarilla leases notify Erwin Elote with the Jicarilla Apache Tribe at least 24 hours (48 hours if possible) before the plugging operations commence. His phone number is (505) 759-3242.

3. Blowout prevention equipment is required.
4. The following modifications to your plugging program are to be made :

Plug # 5: A minimum of 74 sacks of class B cement will be used for this plug.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Rio Puerco Resource Area

435 Montano N.E.

Albuquerque, New Mexico 87107

IN REPLY REFER TO:
NMSF 078911

3162.3-4 (017)

APR 29 1998

Conoco Inc.
10 Desta Drive
Suite 100 W.
Midland, TX 79705-4500

Dear Sir/Madam:

The following conditions of approval must be complied with (as applicable) before the Lindrith B #76 located 1150' FNL & 1750' FWL, section 1, T. 24 N., R. 3 W., can be approved for final abandonment.

1. All fences, production equipment, purchaser's equipment, concrete slabs, deadman (anchors), flowlines, risers, debris and trash must be removed from the location.
2. Any oily soil or fluids must be properly disposed of in an approved disposal area.
3. Pits must be filled in and the edges of the pads shaped to conform to the natural terrain.
4. Pads must be leveled, dressed up by a maintainer, ripped and disked.
5. Access roads must be leveled, waterbarred, disked and blocked off with earthen berms at the junction with the main road and at the entrance to the well pad. Waterbars should be spaced as shown below.

% Slope	Spacing Interval
Less than 2%	200'
2 to 5%	150'
6 to 9%	100'
10 to 15%	50'
Greater than 15%	30'

All waterbars should divert water to the downhill side of the road onto undisturbed ground.

Contact the landowners regarding closure of access roads. Our records indicated that Jack Bechdol is the landowner of the surface for both the well pad and access road.