Fori	n 9-3 eb. 195	31 a (1)	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR

Budget Bureau No.	42-R358.4.
Form Approved.	

Land Office	10.10
Lesse No.	undudit-

Lease No.	130.000=c-
Unit	

SUNDRY NO	OTICES AND REPOR	15 ON W22	
SONDITE		OF WATER SHUT-OFF	
TICE OF INTENTION TO DRILL	CURSEOUENT REPO	DE OF CHOOTING OR ACIDIZATION	
CHANGE PLANS		ar if TEDING LASING	
TECT WAILE 31	HUI-OFF	DE DE DE DRILLING ON INC.	
	KEPAIR III	- DT OC ABANDUNMENT	
	IDIZE	WELL HISTORY	
TICE OF INTENTION TO PULL OR ALTE	IV CALOUR		
TO ABANDON WELL	- 	OTHER DATA)	
/INDICATE /	ABOVE BY CHECK MARK NATURE OF REPORT, NO	OTICE, OR OTHER STATE	
(INDIONIE)			, 19.5 4
	322 4		
	d 736 ft. from $\binom{N}{S}$ line and L	ine of sec.	8
Stevie de	ft. from line and L	850 ft. from W me of	- Arthur ye gray,
ell No is located	u a garage		
	(Range)	(Meridian)	
Sec. and Sec. No.)	(1 wp.)	ew arito	al V
	(County or Subdivision)	(State or Territory)	10.7
apacito (Field)			i.a DK v. ⊛
Cround Colombole	floor above sea level is 7165.	t. Milion	N COM.
u 1 tion of the O能發機製	11001 451	_ P(S)	J. 3 💉
he elevation of the		* *	· · · · /
he elevation of the	DETAILS OF WORK	the of proposed casings; indicate mudding	jobs, cement-
	DE IAILO	ths of proposed casings; indicate mudding	jobs, cement-
State names of and expected depths to	objective sands; show sizes, weights, and lenging points, and all other important proj	ths of proposed casings; indicate mudding posed work) CC CASING AND CHARCE COLOR TO APPROXIMATE	it with
State names of and expected depths to Set minimum of i sacks cement.	DE IAILO	the of proposed casings; indicate mudding posed work) Ce casing and comment of a sproximate productive, to set	it with
State names of and expected depths to Set Minimum of I Sacks cement.	objective sands; show sizes, weights, and lenging points, and all other important projection of 7-5/8" surfaction drill with rotary to 10 drill with r	the of proposed casings; indicate mudding posed work) Ce casing and comment of a sproximate productive, to set	it with
State names of and expected depths to Set minimum of i sacks cemeat.	objective sands; show sizes, weights, and lenging points, and all other important projection of 7-5/8" surfaction drill with rotary to 10 drill with r	the of proposed casings; indicate mudding posed work) ce casing and connection of approximate productive, to set with 150 sacks confirmed and run 2-3/6	jobs, cementat with T. D. approximate ent.
set minimum of 1 sacks cement.	objective sands; show sizes, weights, and lenging points, and all other important projection of 7-5/8" surfaction drill with rotary to 10 drill with r	the of proposed casings; indicate mudding posed work) Ce casing and comment of a sproximate productive, to set	it with T. D. approximate tabis
set minimus of 1 sacks cement. I 3750'ft. To run e sly 3750'ft of 4-1 perforate the 3.	o objective sands; show sizes, weights, and length points, and all other important professions of the first of 7-5/8" surfaction of the first of the	the of proposed casings; indicate mudding posed work) ce casing and comments of approximate productive, to set with 150 sacks of frac, and run 2-3/8	it with T. D. approximate and the control of the co
set minimus of 1 sacks cement. I 3750'ft. To run e sly 3750'ft of 4-1 perforate the 3.	o objective sands; show sizes, weights, and length points, and all other important professions of the first of 7-5/8" surfaction of the first of the	the of proposed casings; indicate mudding posed work) ce casing and comments of approximate productive, to set with 150 sacks of frac, and run 2-3/8	it with T. D. approximate and the control of the co
set minimum of 1 sacks cement. I 3750'ft. To run e sly 3750'ft of 4-1 perforate the 3.	o objective sands; show sizes, weights, and length of the first of the	the of proposed casings; indicate mudding posed work) CC CASING AND CHARGE OOLS to Approximate productive, to set with 150 sacks Colored And Tun 2-3/6	it with T. D. approximate and the control of the co
set minimum of I sacks cement. I 3750'ft. To run e sly 3750'ft of 4-1 perforate the P.	o objective sands; show sizes, weights, and length of the first of the	the of proposed casings; indicate mudding posed work) CC CASING AND CHARGE OOLS to Approximate productive, to set with 150 sacks Colored And Tun 2-3/6	it with T. D. approximate and the control of the co
State names of and expected depths to set minimum of I ancks cement. I 3750'ft. To run e ally 3750'ft of 4-1 Perforate the Perfo	o objective sands; show sizes, weights, and leng points, and all other important professions of the first of 7-5/8" surfactor of the first of 7-5/8" surfactor log to T.D. If 12" casing, and center of Sands, and water over must receive approval in writing by the Gands.	the of proposed casings; indicate mudding posed work) CC CASING AND CHARGE OOLS to Approximate productive, to set with 150 sacks Colored And Tun 2-3/6	it with T. D. approximate and the control of the co
State names of and expected depths to set minimum of I arcks cement. I 3750'ft. To run e ally 3750'ft of 4-1 Perforate the Perfo	o objective sands; show sizes, weights, and leng points, and all other important professions of the first of 7-5/8" surfactor of the first of 7-5/8" surfactor log to T.D. If 12" casing, and center of Sands, and water over must receive approval in writing by the Gands.	rths of proposed casings; indicate mudding posed work) CO CASING AND CHARGE OOLS to Approximate productive, to set of the with 150 sacks Control and Tun 2-3/6	jobs, cementate with T. J. approxies tubis
State names of and expected depths to set minimum of I ancks cement. 3750 ft. To run e aly 3750 ft of 4-1. Perforate the Perforate the Perforate the Abra Address 424-181 and	objective sands; show sizes, weights, and lenging points, and all other important professions of the first of 7-5/8" surfactorized to 1.5. If 100 casing, and came 1/2" casing, and came 2.5 Sands, sand water over must receive approval in writing by the Casing and Back Bldg	rths of proposed casings; indicate mudding posed work) CO CASING AND CHARGE OOLS to Approximate productive, to set of the with 150 sacks Control and Tun 2-3/6	jobs, cementate with T. J. approxies tubis
State names of and expected depths to set minimum of I ancks cement. I are established and set of 4-1 perforate the Perforate th	objective sands; show sizes, weights, and lenging points, and all other important professions of the first of 7-5/8" surfactorized to 1.5. If 100 casing, and came 1/2" casing, and came 2.5 Sands, sand water over must receive approval in writing by the Casing and Back Bldg	the of proposed casings; indicate mudding posed work) CC CASING AND CHARGE OOLS to Approximate productive, to set with 150 sacks Colored And Tun 2-3/6	jobs, cemental with T. J. approxi entrolists tubis