

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS


(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other \_\_\_\_\_  
well well  
2. NAME OF OPERATOR  
JACK CAYIAS  
3. ADDRESS OF OPERATOR  
27209 Kane Lane, Conroe, TX 77302  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17  
below.)  
AT SURFACE: 790'FNL 1850'FWL  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: same  
5. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,  
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input checked="" type="checkbox"/>
(other)	<input type="checkbox"/>

SUBSEQUENT REPORT OF



5. LEASE  
SF-080566-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Stevie Joe - Federal

9. WELL NO.  
# 2

10. FIELD OR WILDCAT NAME  
Tapacito

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 8 T25N-R3W

12. COUNTY OR PARISH Rio Arriba	13. STATE N.M.
------------------------------------	-------------------

14. API NO.  
none

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7175'DF

(NOTE: Report results of multiple completion or zone change on Form 9-350.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

This well, drilled in 1964, was not productive.

Circulate csg with 9.2 gel mud. Cement 3732-3470 plus 40 sx squeeze of perfs 3670-3732. Perf 4½ csg at 3256' and place cement plug inside and outside of csg to 3156. Perf 4½ csg at 170' and cement inside and outside to surface. Cut surface csg 3' below surface if required by landowner. Verbal approval given by Richard Bell July 9, 1981.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set (c) \_\_\_\_\_ Ft.

**18. I hereby certify that the foregoing is true and correct**

SIGNED APPROVED TITLE Agent DATE July 8, 1981

APPROVED BY: AUG 7 1981 TITLE: \_\_\_\_\_ DATE: \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

*For* JAMES F. SIMS  
DISTRICT ENGINEER

\*See Instructions on Reverse Side

NMOCB