



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. HM087657  
Unit \_\_\_\_\_

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		<u>Notice of Spud &amp; Cementing</u>	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 30, 19 60

Well No. 1 Federal is located 1650 ft. from [N] line and 710 ft. from [E] line of sec. 13

SE/4 13 24N 9W RPM

( $\frac{1}{4}$  Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Wildcat San Juan New Mexico

(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 7075 ft.

### DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

The well was spudded 7:30 P.M., July 28, 1960.

160' of 8-5/8" J-55 26# National pipe was set and cemented with 125 sacks regular cement 2% NaCl. Before drilling the plug 500 lbs. pressure was applied on the casing and held for 30 minutes with no drop in pressure. After drilling the plug 500 lbs. was applied on the casing for 30 minutes which showed no drop in pressure.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Ray Smith, Trustee  
Address Simons Building  
Dallas 1, Texas

By G. J. Lilly  
Agent

Title \_\_\_\_\_