

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Senta Fe				
Case No. 978860					
Unit					



		<b>REPORTS</b>	OIA AAFTI	LAUG I IS
NOTICE OF INTENTION TO DRILL	S	UBSEQUENT REPORT OF W. JBSEQUENT REPORT OF SH JBSEQUENT REPORT OF AL JBSEQUENT REPORT OF RE JBSEQUENT REPORT OF AE JBSEQUENT REPORT OF AE	TERING CASINGDRILLING OR REPA -ANDONMENT	IR.
(INDICATE AS	90VE BY CHECK MARK NATURE	OF REPORT, NOTICE, OR O	THER DATA)	
Largo Federal /ell No is located .		line and 660 ft.		of sec. 14
	(Twp.) (Range)	(Meridian	)	
Meti Gallup (Fie d)	(County or Subdivi	sion)	(State or Territo	CO ry)
	ctive sands; show sizes, weight ing points, and all other impo	. Perferation	4: 5057-44	6672.77
7-13, 5123-27, 5150-36, Faxion Cusing Pullers or Madel "K" coment ret con. Max press 2900%.	of Vermal as foll ainer set #5047' Shot cag @4000',	AND Gallup Same:  And perferation  3800° and show  AND TO SAME SAME  AND TO SAME SAME SAME SAME SAME SAME SAME SAME	nd. Plugger to equotical off 02390	by HONCO m
P 5311', 8-5/8" -290', 7-13, 5123-27, 5150-56, Fexico Casing Pellers or Model "K" coment ret com. Max press 2900%. CO #2390' w/100 sx com. w/45 cm. Plug from 16: 1-240'. Com top of sur hole merior.	of Vermal as foll einer set #5047' Shot cog #4000', Com plug from 2 #5'-1555'. Pulle face pipe from 0	and perferation 3800° and show the 3800° and show the 380° and show the 380° and th	nd. Plugger  to equenced  to off 02390'  tiled 5g' to  and can w/30  and install	by HONCO my '. Can by 1685' and on from and regulati
O 5311', 8-5/8" -290', 7-13, 512)-27, 3150-36, Mexico Cusing Pullers or Mexico Cusing Pullers or Mexico Cusing Pullers or Mexico 2908%.  CO 92390' w/100 sx com. w/45 sx. Plug from 16: '-240'. Can top of sur hole merior.  I file supplemental reposit	of Vermal as foll ainer set 85047' Shot cog \$4000', Com plug from 2 85'-1555'. Pullo face pipe from 0	and perferation 3800° and show the 300° and show the 340° and show the 30° a/10° ax	nd. Plugger  to equation of e2390' siled 5g' to  and can w/30 and install  id ready for	by HONCO my '. Cam by '. Cam by '. Ide5' and 'or from .ed regulati
7-13, 5123-27, 5150-36, Mexico Casing Paliers or Mexico Casing Paliers or Mexico Casing Paliers or Mexico Casing Paliers or Mexico Casing Paliers con. Mex press 2900%. Co 92390' w/100 ex con. w/45 ex. Plug from 16: "-240'. Can top of sur: hole mexico.  I file supplemental repr understand that this plan of work must	of Vermal as foll  ainer set #5047'  Shot cog #4000',  Com plug from 2  #5'-1555'. Pullo  fuce pipe from 0  ort when location	and perferation 3800° and show the 300° and show the 340° and show the 30° a/10° ax	nd. Plugger  to equation of e2390' siled 5g' to  and can w/30 and install  id ready for	by HONCO my '. Cam by '. Cam by '. Ide5' and 'or from .ed regulati
7-13, 5123-27, 3150-36, False Clasing Peliers  For Model "K" cement ret.  Com. Max press 2908%.  CO #2390' w/190 sx cem.  w/45 sm. Plug from 16:  "-240'. Com top of sur:  hole merier.  I file supplemental report  understand that this plan of work must	of Vermal as foll  ainer set #5047'  Shot cog #4000',  Com plug from 2  #55'-1555'. Pulle  face pipe from 0  ert when location  receive approval in writing by	and perferation 3800° and show the 300° and show the 340° and show the 30° a/10° ax	nd. Plugger  to equation of e2390' siled 5g' to  and can w/30 and install  id ready for	by HONCO my '. Cam by '. Cam by '. Ide5' and 'or from .ed regulati
70 5311', 3-5/8" -290', 17-13, 5123-27, 5150-56, Mexico Casing Pallers	of Vermal as foll  ainer set #5047'  Shot cog #4000',  Com plug from 2  #55'-1555'. Pulle  face pipe from 0  ert when location  receive approval in writing by	and perferation 3800° and shot 440°-2340°. Fi d cag to 340° at to 30° w/10 ex  is restored as	es squeezed off 62390 illed 5% to mid cam w/30 and install of ready for fore operations may	by HONCO my '. Cam by '. Cam by '. Ide5' and 'or from .ed regulati
Postil . 3-5/8" -290', 7-13, 512)-27, 3150-36, Maxico Cusing Peliers or Model "K" coment retem. Max press 2908%. Co #2390' w/190 sx com. w/45 sm. Plug from 16: "-240'. Com top of sur hole merier.  I file supplemental report understand that this plan of work must mpany	of Vermal as foll  ainer set #5047'  Shot cog #4000',  Com plug from 2  #5'-1555'. Pullo  fuce pipe from 0  ort when location  receive approval in writing by	and perferation 3800° and shot 440°-2340°. Fi d cag to 340° at to 30° w/10 ex  is restored as	nd. Plugger  to equation of e2390' siled 5g' to  and can w/30 and install  id ready for	by HONCO my '. Cam by '. Cam by '. Ide5' and 'or from .ed regulati