

APPROVED
Form 9-31a
(Feb. 1951)

Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.

(SUBMIT IN TRIPLICATE)

Land Office Santa Fe
Lease No. S. F. 079422
Unit Hawai Bolack

AUG 13 1956
JERRY W. LONG
ACTING DISTRICT ENGINEER

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Hawai Bolack August 13, 1956

Well No. 1 is located 660 ft. from SW line and 660 ft. from E line of sec. 5

SE 1/4 - SE 1/4 Section 5 24N 11W N. M. P. M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Wildcat San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 4383 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set cement plugs as follows: 5300' to 5450' - 3600' to 3700' - 1350' to 1450' - 950' to 1050' - 385' to 455' - 25' set in top of 10-3/4" surface casing.
Placed permanent marker - 4" pipe, 4' above surface.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Stally Oil Company

Address Box 426

Farmington, New Mexico

Marginal E. A. Cooper

By _____

Title District Foreman

