

Form 9-331a
(Feb. 1951)


(SUBMIT IN TRIPLICATE)

Land Office **Santa Fe**Lease No. **078301**

Unit

RECEIVED

NOV 5 1959



Section 1

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

U. S. GEOLOGICAL SURVEY

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Federal 9-1

November 2

1959

Well No. **2** is located **1980** ft. from **10N** line and **660** ft. from **10W** line of sec. **1**
SW 1/4, NE 1/4, Section 1 **24N** **10W** **NMPM**
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Dist. Lower Gallup **San Juan County** **New Mexico**
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6968** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

A radioactive tracer survey was run which indicated that the perforations 5170'-5192' were taking 100% of the fluid. A bridge plug was set at 5165' and the interval 5140'-5155' was fraced with 15,000 gal. crude and 30,000 lbs. sand at 2200 psi and 37 B PM. The plug was pulled and the well was placed on production.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.
Standard Oil Company of Texas

Company

P.O. Box 1581

Address

Farmington, New Mexico

By

Field Foreman

Title