Form 9-331 (May 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR (Other in verse side) GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE. instructions on reForm approved. Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

14-20-603-126*t* 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo Tribe

SUNDRY NOTICES A	AND	REPORTS ON	1 N	/ELLS
(Do not use this form for proposals to di	rill or to	deepen or plug baci	to a	different reservoir.

Use "APPLICATION FOR PERMIT-" for such proposals.)

7. UNIT AGREEMENT NAME WELL Water Injection Well East Bisti Unit OTHER 8. FARM OR LEASE NAME

NAME OF OPERATOR Skelly Oil Company

3. ADDRESS OF OPERATOR 9. WELL NO. 81

1860 Lincoln Street - Denver, Colorado LOCATION OF WELL (Report location clearly and in accordance with any State requirements. 10. FIELD AND POOL, OR WHIDCAY

Bisti Lover Gallun 11. SEC., T., E., M., OR BLK. AND SURVEY OR AXEA

684' FNI. & 1980' FWL Section 4-24N-10W

Section 4-24N-10W

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6871' DF

12. COUNTY OR PARISH | 13. STATE San Juan New Mexico

16

REPAIR WELL

(Other)

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

PULL OR ALTER CASING TEST WATER SHUT-OFF FRACTURE TREAT MULTIPLE COMPLETE SHOOT OR ACIDIZE ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF: REPAIRING WELL WATER SHUT-OFF ALTERING CASING FRACTURE TREATMENT SHOOTING OR ACIDIZING ABANDON MENT

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated late of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

All depths shown are from Ground Level.

8/21/71 MIGRU Aztec Well Servicing Unit. No rods in hole.

Spotted cement plug from 5388 to 5288 . Pulled 2" tubing.

Worked 5 1/2" casing to free same. Rigged up Blue Jet, perforated casing from 1740' to 1739' w/4 shots. Spotted cement plug from 1740' to 1590'. Pulled 2" tybing. Shot 5 1/2" casing off at 980'. Spotted cement plug from 1030' to 910', 50' inside casing and 70° above 5 1/2" casing stub.

Pulled 24 joints 983' of 5 1/2" casing.

Spotted 10' cement plug in surface casing. Installed dry hole marker. Completed P&A 8/21/71.

8. I hereby certify that the foregoing is true and cor	rect	
SIGNED 6 9 Biffel	TITLE Lead Clerk	Date December 10, 1971
(This space for Federal or State office use)		
APPROVED BY	TITLE	DATE
CONDITIONS OF APPROVAL, DE ANY:		