Form 9-331 Form Approved. Dec. 1973 Budget Bureau No. 42-R1424 UNITED STATES Soffice Soffin Soffin Soffin ខ្លួកគ 5. LEASE DEPARTMENT OF THE INTERIOR ឆ៊ុំ≦ត្ NM 16456 **GEOLOGICAL SURVEY** 6. IF INDIAN, ALLOTTEE OR TRIBE NAME eted, c 7. UNIT AGREEMENT NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) N/A ings of 8. FARM OR LEASE NAME 2 5 6 6 1. oil Federal gas of tog well well other # 7 E 9. WELL NO. 2. NAME OF OPERATOR 1-30 broz Kirby Exploration Company 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR <u>Wildcat</u> P.O. Box 1745; Houston, Texas 77001 11. SEC., T., R., M., OR BLK. AND SURVEY OR stuce. 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 AREA Sec 30.T24N.R8W AT SURFACE: 790' FSL & 1710' FEL 12. COUNTY OR PARISH 13. STATE & AT TOP PROD. INTERVAL: New Mexico San Juan AT TOTAL DEPTH: Table of the second of the sec ido it biniti biniti biniti 14. API NO. 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6845 G.L. 소문을 표 등 및 설립 경 REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: Compared of American Compared hogen bar any State copies t TEST WATER SHUT-OFF ž. FRACTURE TREAT SHOOT OR ACIDIZE 43 REPAIR WELL (NOTE: Report results of multiple completion or zone encitarego Hew less to be before to be the second to be t PULL OR ALTER CASING change on Form 9-330. bní bluede ta Bo Bobb dhait Bo bobb dhait Bo aid bha ta MULTIPLE COMPLETE **CHANGE ZONES** nsitni ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 왕 등목**등 8** The subject well has been adequately tested & proven to be non-commercial a Refer to sundry notices of water shut off for cement data. Long string was cemented w/200 sks class "B" w/good circulation through out entire job. Calculation based on 75% fill indicate cement top to be 302' & 100% fill fring proposed the We propose to plug the well as follows: Spot 25 sk class "B" cement plug from 1500'-1700'. Spot 30 sk class "B" cement plug from 950'-1200'. mdua val lare o anoit woled r Spot 10 sk class "B" cement plug from 0-60'. due for ead Pump 5 sk class "B" cement in 4½" x 8 5/8" annulus Install dry hole marker. Restore location to U.S.G.S. & BLM specifications A St. Subsurface Safety Valve: Manu. and Type Ft. in to apply the 18. I hereby certify that the foregoing 9 is true and correct fitLE Agent SIGNED t PidT: 4113 to not This space for Federal or State office use Ö MAR 2 9 1978

*See Instructions on Reverse Side

TITLE

<u>0</u> ±

10 (Fed

9

the several control of the control o

Ē,

contibbe at the contibbe at th

DATE



APPROVED BY

CONDITIONS OF APPROVAL

ACTING DISTRIC. ENGINEER