

Form 3160-5  
(June 1990)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

## SUBMIT IN TRIPLICATE

## 1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other P&A

## 2. Name of Operator

Dugan Production Corp.

## 3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

## 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1710' FSL &amp; 1900' FEL (NW/4 SE/4)

Unit J, Sec. 25, T24N, R8W

## FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

## 5. Lease Designation and Serial No.

NOO-C-14-20-8452

## 6. If Indian, Altonce or Tribe Name

Navajo

## 7. If Unit or CA, Agreement Designation

## 8. Well Name and No.

South Blanco Navajo 25#3

## 9. API Well No.

30 045 25063

## 10. Field and Pool, or Exploratory Area

Lybrook Gallup

## 11. County or Parish, State

San Juan County, NM

## 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## TYPE OF SUBMISSION

☐ Notice of Intent☐ Subsequent Report☒ Final Abandonment Notice

## TYPE OF ACTION

☐ Abandonment☐ Recompletion☒ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

## 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well was plugged as follows:

- 1.) Set CIBP @ 5401'. Capped with 8 sks class "B" cement.
- 2.) Pull tubing to 3217'. Rig up Wireline. Run perforating gun and perforate Mesa Verde @ 3523'. TIH with tubing to 3526'. Spot 51 sks class "B" cement. Pull up hole. Displaced cement to 3373' with water. Reached 800 psi pressure.
- 3.) Pulled up to 1997'. Spotted 55 sk class "B" plug inside casing. Top of plug at 1271'.
- 4.) Pulled up to 344'. Filled casing full to surface with 45 sks class "B" cement.
- 5.) Cut off wellhead and set dry hole marker.

Job complete 3/12/96.

## 14. I hereby certify that the foregoing is true and correct

Signed Gary Brink  
(This space for Federal or State office use)Title Operations ManagerDate 3/13/96Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_

Date \_\_\_\_\_

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

NMOCB