

Form 3160-5
(November 1983)
(Formerly 9-331)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTSUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		3. LEASE DESIGNATION AND SERIAL NO. NM-22044	
2. NAME OF OPERATOR DUGAN PRODUCTION CORP.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P. O. Box 208, Farmington, NM 87499		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL - 1980' FWL		8. FARM OR LEASE NAME Gold Medal	
14. PERMIT NO.		9. WELL NO. #6	
15. ELEVATIONS (Show whether OF, ST, CR, etc.) 6535' GL; 6547' RKB		10. FIELD AND POOL, OR WILDCAT South Bisti - Gallup	
		11. SEC., T., R., M., OR BLM, AND SURVEY OR AREA Sec. 31, T24N, R10W, NMPM	
		12. COUNTY OR PARISH San Juan	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Spud, Surface Casing & Test ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

M.I. & R.U. Four Corners Drilling Company Rig #5. Spudded a 12-1/4" hole @ 12:45 PM 12-24-87. Drilled to 215'. Ran 10 jts. 8-5/8" OD, 24#, 8 Rd, ST&C casing (T.E. 188.75') set @ 201' RKB. Cemented with 135 sx class "B" + 2% CaCl₂ (159 cf). P.O.B. @ 5:15 PM 12-24-87. Circulated 1 bbl cement to surface. Shut down 26 hrs. for Christmas Day. Nipped up BOP and tested surface casing and BOP to 600 psi for 30 minutes - held OK. Resumed drilling at 4:15 AM 12-26-87.

RECEIVED
BLM MAIL ROOM
88 JAN -4 PM 2:05
FARMINGTON RESOURCE AREA
FARMINGTON, NEW MEXICO

JAN 16 1988

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. JacobsTITLE GeologistDATE 12-29-87

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

NMOCC

*See Instructions on Reverse Side