10

Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

PORM APPROVED		
Budget Bun	eau No.	1004-0135
Expires:		

5.	Lease	Design	netice	and	Serial	No

SUNDRY NOTICES AND R	REPORTS ON	WELLS
----------------------	------------	-------

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

SF 078868 6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

1. Type of Well Oil Gas Well Well Other		
		8. Well Name and No.
2. Name of Operator		Sapp #93
Dugan Production Corp.		9. API Well No.
3. Address and Telephone No.		30 045
P.0∑Born420 Farmington,		10. Field and Pool, or Exploratory Area
4. Location of Wall (Fortige, Sec. F., R., M., or Survey D		Basin Fruitland Coal
1356 FNL 1990 FEL (SW/4)	NE/4)	11. County or Parish, State
Unit S Sec. 29, T24N, R8W		San Juan County, NM
12. CHECK APPROPRIATE BOX	s) TO INDICATE NATURE OF NOTICE, RI	EPORT, OR OTHER DATA
TAPE OF SURMISSION	TYPE OF AC	TION
Notice of Intent	Abandonment	Change of Plans
Subsequent Report	Recompletion Plugging Back	New Construction Non-Routine Fracturing
Final Abandonment Notice	Casing Repair Altering Casing	Water Shut-Off Conversion to Injection
	A Other <u>Amend APD</u>	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
 Describe Proposed or Completed Operations (Clearly state al give subsurface locations and measured and true vertice) 	pertinent details, and give pertinent dates, including estimated date of all depths for all markers and zones pertinent to this work.)	starting any proposed work. If well is directionally drilled,

Amend approved APD as follows:

- 1. Drill 124" hole and set 8-5/8" 24 lb. K-55 surface casing at
- 2. Cement surface with 100 cu. ft. Class B + 2% Cap 2. Circulate to surface.
- 3. Drill 7" hole to 1740' using same drilling configuration as approved APD.
- 4. Set 53" 15.5 lb. K-55 casing at 1740'.
- 5. Cement with 150 cu. ft. 2% Lodense + 1 lb./sk celloflake, followed by 70 cu. ft. Class $B + \frac{1}{4}$ lb./sk celloflake. Cement to surface.
- 6. Drill 4-3/4" hole to 1800' using same drilling configuration as approved in APD for upper hole.

Fitle 18 U.S.C. Section 1001, makes it a crime for any person knowled representations as to any matter within its jurisdiction.	ingly and which is any department or agency of the Un	nited states any fairer, fiction of haddlet salarious
Constant of Spirits, a my.		QCT 3 U 1995
Approved byConditions of approval, if any:	Title	A-PPROVED
Signed	Tide <u>Operations Manager</u>	
1715' - 1800'.	K-55 perforated liner acro	_