

天

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **081221-B**
Unit **Bolack**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	X
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 3 19 **62**

Well No. 1 is located 1080 ft. from 2N line and 1920 ft. from E line of sec. 9
SW/4 SE/4 Sec. 9 26N 1W N.M.P.M.
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat Rio Arriba New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 7770 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

6-28-62 Spudded in 17 $\frac{1}{2}$ " hole.

6-29-62 TD 310' NKB. Set 9 joints 292' of 13-3/8" OD 48# H-40 casing at 306' NKB with 350 sacks cement, 2% calcium chloride.

6-30-62 Pressured up on casing to 500# for 30 minutes. No decrease in pressure.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company BOLACK, GREER ET AL
Address 158 Petroleum Center Bldg.
Farmington, New Mexico

By Thigit J. Woods
Title Engineer