

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. 079071  
Unit W/2

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	<input type="checkbox"/>	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	<input type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 1, 1957, 19

Schultz-Canyon Largo Unit

Well No. 1-28 is located 1,650 ft. from N line and 1,450 ft. from W line of sec. 28

NW/4 Section 28  
(1/4 Sec. and Sec. No.)


T 25-North R-6-West  
(Twp.) (Range)

N.M.P.M.  
(Meridian)

Canyon Largo P. C.  
(Field)

Rio Arriba County  
(County or Subdivision)

New Mexico  
(State or Territory)



The elevation of the derrick floor above sea level is 6,739 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

West half of Section 28 is dedicated to this well. (SW/4 on Santa Fe 079071-A)

Propose to spud with "shot hole" rig; then drill with rotary tools to the bottom of the Pictured Cliffs formation - the top of which is expected at about 2,700 feet. Completion with cable tools - and sand fracturing, hydro-fracturing, and/or shooting with solidified nitro-glycerin as conditions warrant.

Casing program: 90 feet of 8-5/8" new 8 rd. thd. 24# casing. Circulate cement to surface, using at least 70 sacks cement.

5-1/2" OD J-55 - 14# or better casing - to be set through Pictured Cliffs formation - cemented with 100 sacks regular cement. Casing to be perforated for hydro-fracturing, etc.

1" tubing to be set within 20 feet of total depth for production.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Frank A. Schultz, Jr.

Address Box 728

Farmington, New Mexico

By C. Beeson Neal  
C. Beeson Neal, Agent in Farmington  
Title \_\_\_\_\_

Faint header text at the top of the page, possibly including a date or reference number.

Second section of faint text, appearing as several lines of a letter or document.

Third section of faint text, continuing the document's content.

Fourth section of faint text, possibly containing a list or specific details.

Fifth section of faint text at the bottom of the page, possibly a signature or footer.