

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 067988
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

_____ January 3, 1962

USA T. J. Foster

Well No. 1 is located 1820 ft. from [N] line and 1830 ft. from [E] line of sec. 7

NE/4 Sec. 7 25 N 7 W N.M.P.M.

(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Basin Dakota Rio Arriba New Mexico


(Field) (County or Subdivision) (State or Territory)

The elevation of the ~~destination~~ ground level above sea level is 6498 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Ran and cemented production casing as follows:
Ran 213 joints of 5-1/2", 14# and 15.5#, J-55 casing and set at 6937'. Stage collar set at 2404' and cemented in two stages. First stage: cemented with 300 sacks Incor with .9% Haled 9. Second stage: cemented with 50 sacks Incor-Pomix 1:1 with 6% gal. WOC 24 hours. Pressure tested casing to 3000 pounds for 30 minutes. Pressure held o.k.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Tenneco Oil Company

Address P. O. Box 1714

Durango, Colorado

By L. B. Plumb

Title District Production Superintendent