

APPROVED JUN 1 1956Budget Bureau 42-R308.2
Approval expires 12-31-52(Orig. Sgd.) J. W. LONG
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Santa Fe
Lease No. 080375
Unit Sheets

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	Subsequent Report of Sand-oil Treatment	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 25th, 1956


Well No. 6 is located 790 ft. from N line and 1125 ft. from E line of sec. 6SW/4 SW/4 Sec. 6
(1/4 Sec. and Sec. No.)25N
(Twp.)7W
(Range)N.M.P.M.
(Meridian)Ballard
(Field)Rio Arriba
(County or Subdivision)New Mexico
(State or Territory)The elevation of the derrick floor above sea level is 6946 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

5-9-56 TD 2866'. Plugged back to 2773' with hydromite. Sand-oil treated from 2742' to 2773' with 11,000 gallons diesel oil and 18,500# sand, flushed with 2,800 gallons diesel oil. Breakdown pressure 3000#, treating pressure 1400#, injection rate 34.3 BPM. Set Baker 2B CI bridging plug at 2720'. Perforated 2704' to 2676' with 4 shots per foot. Sand-oil treated through perforations with 10,780 gallons diesel oil and 9,792# sand, flushed with 2,700 gallons diesel oil. Maximum treating pressure 2500#, injection rate 36.6 BPM. Before treatment gas too small to measure. After treatment 2,700 MCF/day.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company BENSON-MONTINAddress 405 1/2 West BroadwayFarmington, New MexicoBy [Signature]
Title Field Superintendent

