

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

RECEIVED
DEC - 8 1995

2. Name of Operator
MERIDIAN OIL

OIL CON. DIV.
DIST. 3

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1850' FNL, 1650' FEL, Sec.32, T-26-N, R-4-W, NMPM

- 5. Lease Number
Jic Contract 120
- 6. If Indian, All. or Tribe Name
Jicarilla Apache
- 7. Unit Agreement Name
- 8. Well Name & Number
Jicarilla 120 C #11
- 9. API Well No.
30-039-06237
- 10. Field and Pool
Basin Fruitland Coal/
So Blanco Pictured Cliff
- 11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action	
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

11-6-95 MIRU. SDON.
 11-7-95 ND WH. NU BOP. PT BOP. TOO H w/104 jts 2 3/8" tbg. TIH to 3263'. Pump 20 bbl wtr down tbg. Plug #1: pump 65 sx Class "B" cmt w/2% calcium chloride @ 2587-3263' WOC. TOO H to 1754'. WOC. PT csg to 500 psi, failed. TIH, tag TOC @ 2716'. Perf 3 sqz holes @ 1817'. TIH w/5 1/2" cmt retainer, set @ 1754'. PT tbg to 1500 psi, OK. PT csg, failed. Establish injection. Plug #2: pump 40 sx Class "B" cmt below cmt retainer outside csg @ 1717-1817', leave 9 sx on top of cmt retainer, TOC @ 1660'. TOO H. Perf 3 sqz holes @ 178'. Establish circ down csg & out bradenhead w/5 bbl wtr. Plug #3: pump 67 sx Class "B" cmt down csg from 178' out bradenhead. Circ 1 bbl cmt to surface. WOC. SDON.
 11-8-95 ND BOP. Cut off WH. Fill 5" csg w/2 sx Class "B" cmt. Install dry hole marker w/8 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 11-8-95.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 11/14/95

(This space for Federal or State Office Use)
APPROVED BY [Signature] Title Chief Lands and Mineral Resources Date DEC 7 1995

CONDITION OF APPROVAL, if any: