

**NORTHWEST PRODUCTION CORPORATION**

ALBUQUERQUE, NEW MEXICO

March 12, 1962

REPLY TO:  
520 SIMMS BUILDING  
ALBUQUERQUE, NEW MEXICO

Oil Conservation Commission  
State of New Mexico  
1000 Rio Brazos Road  
Aztec, New Mexico

Attention: Mr. Emery C. Arnold

Gentlemen:

Your letter of March 5, 1962 requested that our "C" well #2-29 in Unit L, Section 29, Township 26 North, Range 4 West be scheduled for 1961 packer leakage test.

In November, 1959 a plug was set in the 2-3/8" OD Dakota tubing in "C" well #2-29, and the tubing was perforated above the plug from 5589'-90'. The Dakota zone was temporarily abandoned at this time. Inasmuch as the Mesaverde has been logged off for most of the past year, we plan to permanently abandon this well when weather permits.

Very truly yours,

NORTHWEST PRODUCTION CORPORATION

*Ray Phillips*  
Ray Phillips, Manager  
Production Operations

RP/jap



(SUBMIT IN TRIPLICATE)

Indian Agency JicarillaUNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Contract #120

Allottee

Lease No.

	29	
x		

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 4, 1953

Well No. C 2-22 is located 1830 ft. from N line and 870 ft. from E line of sec. 29

NW/4 SW/4 29 (1/4 Sec. and Sec. No.) 26N (Twp.) 4W (Range) NMP (Meridian)

Blanco MV and Basin DK (Field) Rio Arriba (County or Subdivision) New Mexico (State or Territory)

The elevation of the ~~ground~~ <sup>ground</sup> floor above sea level is 5775 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TD 7852'. Both Mesaverde and Dakota formations were marginal prior to logging off. Only with periodic swabbing could either zone be produced and this practice is not economical. Propose to spot 35 sx cement plug in 5" casing from 7852-7900; 70 sx cement plug in 5" casing from 3600-4900. Salvage as much 7" casing as possible. Spot 100' cement plug (30sx) from 50' above 7" stub to 50' inside 7". Spot 10 sx cement plug at surface with dry hole marker.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company NORTHWEST PRODUCTION CORP.Address BOX 1796EL PASO 49, TEXAS

By

Title Ray Phillips, Mgr., Prod. Oper.