

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

ENERGEN RESOURCES CORPORATION

3. Address and Telephone No.

2198 Bloomfield Highway, Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FSL, 1190' FWL, Sec. 30, T26N, R4W, N.M.P.M.

5. Lease Designation and Serial No.

Jic Cont 120

6. If Indian, Allottee or Tribe Name

Jicarilla Apache

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Jicarilla 120C

9

9. API Well No.

30-039-06298

10. Field and Pool, or exploratory Area

S. Blanco PC

11. County or Parish, State

Rio Arriba

NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was plugged and abandoned as follows:

1. TOH. TIH with CIBP set at 3100'.
2. Spotted 50 sks Class B cement on top of plug. TOH.
3. Perfed 2 squeeze holes at 1730'. TIH to 1730'. Spotted 35 sacks Class B cement with 2% CaCL2. Pull out of cement. Displace 4 1/2 BBLS to top of 1580'. TOH.
4. Perfed 2 squeeze holes at 194'. Pumped 65 sks Class B filling casing full inside and out to surface. Cut off wellhead.
5. Installed dry hole marker.

NOTE: PLUGGING WAS WITNESSED BY ERWIN ALOTTEE - JICARILLA COMPLIANCE OFFICE.

14. I hereby certify that the foregoing is true and correct

Signed Alan Graham

Title Drilling Foreman

Date 11/1/99

(This space for Federal or State office use)

Approved by Petro. Eng.

Title

Date 12/22/97

Conditions of approval, if any: