

(SUBMIT IN TRIPLICATE)

Indian Agency Alamogordo

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee Alamogordo Tribal

Lease No. Contract 108

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		<u>Subsequent Report of Sandfree</u>	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 14th, 1957

Well No. 1-6 is located 990 ft. from [E] line and 1190 ft. from [W] line of sec. 23
SW/4 SW/4 Sec. 23 26N 5W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wilcox Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6561 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

3- 2-57 PROD 3100'. Perforated from 3072' to 3087' and from 3026' to 3030' with 4 holes per foot.

3- 4-57 Treated with 200 gallons HGA. Sandfrased through perforations with 26,500 gallons water and 30,000/ sand, flushed with 3,500 gallons water. Breakdown pressure 1300#, treating pressure 1000#, average injection rate 36.5 barrels per minute.

3- 6-57 After 36 hours flowing 2,194 MCF/day.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced

Company EL PASO NATURAL GAS COMPANY

Address Box 997

Farmington, New Mexico

By E. J. [Signature]
Title Senior Petroleum Engineer



