Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED

	** (2) 11	Q 4 LU	
ludget Bur	eau No.	1004-013	٤
Expires:	March:	31, 1993	

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.]*

5. Lease Designation and Serial No.

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.		SF-079318		
Use "APPLICATIO	Use "APPLICATION FOR PERMIT - " for such proposals			
		7. If Unit or CA, Agreement Design	nation	
. Type of Well Ges Other		8. Well Name and No.		
. Name of Operator	Attention:	REAMS A LS #1		
AMOCO PRODUCTION COMPANY	WAYNE BRANAM	9. API Well No.		
3. Address and Telephone No.		30-039-06386		
P.O. Box 800, Denver, Colorado 80	201 (303) 830-4912	10. Field and Pool, or Exploratory Area		
Location of Well (Footage, Sec., T., R., M., or Survey Description)		WILDCAT		
1650'FSL 1650'FEL	J Sec. 24 T 26N R 6W	11. County or Parish, State		
		RIO ARRIBA	NM	
. CHECK APPROPRIATE	BOX(s) TO INDICATE NATURE OF NOTICE, F	EPORT, OR OTHER DA	TA	
TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent SEP1 Subsequent Report Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection	RECEIV	

041793 MIRUSU. KILL WELL W/80 BBLS OF FW, TIH W/ CMT RET AT 3050', PULL OUT OF RET AND PRESS TST CSG TO 1000#, DID NOT TEST, HAVE LEAK ABOVE RET TO SURF. STING INTO RET. PREP TO CMT TO SQZ OPEN HOLE, SPOT CMT PLUG AND LOCATE CSG LEAK. MIX AND PUMP 63 SKS 65/35 2% GEL CMT, SQUEEZE OPENHOLE BELOW RET AT 3028', PULL OUT RET SPOT 123 SKS 65/35 2% GEL TO 1900', TOH LAY DN 26 JTS TBG. TOH PU PKR TIH SET PKR AT 1088', TEST CSG FROM 1088' TO 3028' TO 1000# HELD. TIH TO 1900' SPOT 17 SKS MUD FROM 1900' TO 1200', TOH LAY DN 36 JTS TBG, TIH PERF AT 1200' W/4 SHOTS, TOH. TIH W/ CMT RET AT 1088', ATTEMPT TO CIRC SURF, SOME SMALL RETURNS THAT QUIT, RECEIVED VERBAL APPROVAL FROM BLM, WAYNE TOWSEND ON 042093, TO PUMP A 100' PLUG PLUS 100% EXCESS BELOW RET, PULL OUT AND CIRC SURF OUT

RET AT 1088', PULL OUT RET A BRAIDENHEAD (123 SKS INSIE CSG AND BRAIDENHEAD TO S SD PREP TO RDMOSU 042193	AND PUMP 152 SKS CLS DE CSG, 29 SKS OUTSIDI	B NEAT CMT CIRC GOOD E) TOH LAY DN TBG, NDB	CMT OUT OP, TOP OFF	
4. I hereby certify that therforegoing is true and correct Signed Wayn P	Title	BUSINESS ANALYST	Date	08-27-1993
his spece for Federal or State office use) Approved by Conditions of approvel, if any:	Approved as to plugging Liability under bond is surface restoration is	completed.	SEP	ROVED
tle 18 U.S.C. Section 1001, makes it a crime for any person knowingly an presentations as to any matter within its jurisdiction.	nd willfully to make to any department o	r agency of the United States any false, fict	ticious, of fraudulent	T MANAGER
CO	* See Instructions on Re	verse Side		