## STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

## **OIL CONSERVATION DIVISION**

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	·	BIL PRODUCI	NG TX. & N.M.	INC. Lease _	.licarilla B		Wo		
Location of Well:	Unit A	Sec. <u>19</u>	Twp. 26N	Rge		Cou	inty <u>Ri</u>	o Arribba	
NAME OF RESERVOIR OR POOL			TYPE OF F	TYPE OF PROD. (Oll or Gae)		D.	PROD. MEDIUM (Tbg. or Csg.)		
Upper Completion Tapacito Pictured Cl			d Cliffs	liffs Gas		Flow		TBG	
Completion Blanco Mesa Verde			2	Gas		Flow		TBG	
			PRE-FL	OW SHUT-IN P	RESSURE DATA				
Upper	Hour, date s		Length of lime sh	ut-in	Si press. psig		Stabilized?	(Yes or No)	
Completion 8:40 10-29				ays '			yes		
Lawer Completion	HOUT, DETE S	5-29-90	Length of time sh	. 5 mo.	SI press. paig		Stabilized?	(Yes or No)	
	<u> </u>	3 23 30	<u> </u>	FLOW TEST			<u>i y</u>	<u> </u>	
Consmenced	at (hour, dat	12-8-91	····	HOW IEST	Zone producing (Up	oper or Lowert T	OWER		
TIME (hour, date)		LAPSED TIME SINCE*		SURE	PROD. ZONE				
			Upper Completion	Lower Completion	TEMP.	REMARKS			
12-9-9	91	lst day	405#	120#	date	1 0 4 9	0:3	<b>30</b> 2-7-91	
12-10-91		2nd day	404#	120#	upper	435#		435#	
					lower 📆	):120##	3 yê <del>b</del> aty	120#	
						March & Reco	aren ja	A SO YIVE	
					19	1 304 3000			
roductio	n rate di	iring test							
Oil:		BOPI	D based on	Bbls. in	Hours	G		GOR	
Gas:	90		MCF	PD; Tested thru	(Orifice or Meter	): <u>METER</u>			
				ST SHUT-IN PR					
Upper Completion			<del></del>			Si press. paig		Stabilized? (Yes or No)	
<del></del>			Length of time shu	Length of time shut-in		SI press, paig		Stabilized? (Yes or No)	

DEC3 01991
OIL CON. DIV

(Continue on reverse side)

FLOW TEST NO. 2

mmenced at (hour, da	(10) 水本		Zone producing (Upper or Lower):				
TIME	LAPSED TIME	PRESSURE  Upper Completion Lower Completion		PROD. ZONE	REMARKS		
(hour, date)	SINCE **	Upper Completion	Lower Completion	icmr.		in the contract of the contrac	
<del></del>	·						
oduction rate o	luring test				•		
il:	BOF	D based on	Bbls. in	Hours	Gra	v GOR	
ıs:		мсі	PD: Tested thru	Orifice of Meter	r):		
marks:					•.	<del></del> .	
hereby certify t	hat the informat	ion herein contair	ned is true and con	nplete to the be	st of my knowl	edge.	
pproved	DEC 30	1991				PROD. U.S. INC.	
Mem Wexico C	Oil Conservation	DIAI210II	В	yX	Z/Hoyd		
y	inal Signed by CH	ARLES GHOLSON	Tide PRODUCTION TECH. I				

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever temedial work has been done on a well during which the packer or the rubing have been disrurbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

DEPORT OF E CAS INSPECTOR DIST AS

Title

- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packet leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shur-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the aumosphere due to the lack of a pilpeline connection the flow period shall be three hours.
- 3. Following completion of Flow Ten No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Printeduct for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period, 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tents: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be therefore at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Azter District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

