



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Santa Fe
Lease No. NM 046-A
Unit #1 Humble-Federal "B"

SUNDRY NOTICES AND REPORTS ON WELLS

| | |
|--|--|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | SUPPLEMENTARY WELL HISTORY |
| NOTICE OF INTENTION TO ABANDON WELL | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 27, 19 60

Humble-Federal
Well No. #1-"B" is located 880 ft. from S line and 1030 ft. from W line of sec. 16SW/4 Section 16
(1/4 Sec. and Sec. No.)26N
(Twp.)2W
(Range)100M
(Meridian)Undesignated
(Field)Rio Arriba
(County or Subdivision)New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 7258 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Plugged and abandoned September 16, 1960
Pulled 61 joints or approximately 2000' of 7-5/8" casing.
Set cement plug from 5600' to 6058'
Set plug at top of 7-5/8" casing w/10 sz. cement.
Set plug at 1500-1650' w/30 sz. cement.
Set plug at bottom of surface pipe at 307' w/10 sz. cement.
Set plug at top of surface pipe w/10 sz. cement.
Set marker on surface.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Cabot Carbon CompanyAddress 750 Petroleum Club Bldg.Denver 2, Colorado

By _____

Title District Geologist