

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR
Caulkins Oil Company

3. ADDRESS OF OPERATOR
P.O. Box 780 Farmington, New Mexico

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 965' From South & 1125' From East
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

AUG 22 1983

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

5. LEASE

NM 03733

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Breech

9. WELL NO.
310

10. FIELD OR WILDCAT NAME
South Blanco Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 13, 26 North, 7 West

12. COUNTY OR PARISH
Rio Arriba

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6155 DF

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-2-83 Ran Cement Bond Log.
Found cement covering Alamo. Cement top 120'
Perforated 2 holes in 5 1/2" Casing at 126'.
Ran 2 3/8" Tubing to 2400'.
Spotted cement 2400' to 2100'. (41 Cu.Ft.)
Spotted 9# Gel Based Mud 2100' to 1900'.
Spotted Cement Plug inside pipe 1900' to 1550'. (58 Cu.Ft.)
Spotted 9# Gel Based Mud 1550' to 1200'.
Spotted Cement Plug 1200' to 900'. (41 Cu.Ft.)
Spotted 9# Gel Based Mud 900' to 126'.
Circulated Cement surface to 126' (perforations) and back
to surface thru Bradenhead. (Over)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Charles E. Vergara TITLE Superintendent DATE DEC 13 1983

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

NMOCC

*See Instructions on Reverse Side

RECEIVED
DEC 18 1984
OIL CON. DIV.
DIST. 3

APPROVED
AS AMENDED

DEC 14 1984
J. Stan McKee
M. MILLENBACH
AREA MANAGER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

8-3-83

Built Monument.

A 4 1/2" X 10' Monument has been welded to top of Surface Casing then hole filled with gravel.

Monument is permanently inscribed with following information:

Caulkins Oil Company
Well No. Breech 310
Lease No. NM 03733
SE 1/4 SE 1/4 Sec. 13 26N 7W
Rio Arriba County, New Mexico

Surface will be cleaned, bar ditches built and reseeding done before September 1, 1983.

Sunray Notice will be filed when Location is ready for inspection.