Budget				
Approv	al expir	es 12-	-31-60.	

(A)	pril 19	62)	
	1	6	
	•	O	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

White artistes re-et-or
Indian Agency Jicarilla
Apache
Allottee
Lease No. 116,

NUMBER OF INTE	NTION TO DRILL	SUBSECUENT REPORT OF WATER SHUT-OFF.
	NTION TO DRILLNTION TO CHANGE PLANS	SUBSEQUENT REPORT OF WATER SHUT-OFF
	NTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
	NTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
	NTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
	NTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY.
NOTICE OF INTE	NTION TO ABANDON WELL	
	(Indicate above by Check M/	IRK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	. •	September 16 , 19_63
Apa	ache	(SA)
/ell No4	-16 is located 1850 ft.	from ${\mathbb{N} \atop S}$ line and 1850 ft. from ${\mathbb{E} \atop W}$ line of sec. 16
		(~)
	16 26 N (Twp.)	(Range) NMPM (Meridian)
<u> Basin Dak</u>		o Arriba New Mexico
ση Γapicito F	old) (Cou Pictured Cliffs	nty or Subdivision) (State or Territory)
	of the derrick floor above sea	level is 7137 ft. KB
		7125 GL
	DET	'AILS OF WORK
		r sizes, weights, and lengths of proposed easings; indicate mudding jobs, comeat all other important proposed work)
oudded 3/8 emented w own at 1:30 5706' KB iacel, 25 own at 10: ad stage w	3/63. Drilled 15" hole with 260 sacks of regular 0 A.M., 3/9/63. Drill 1, stage collar at 3960's sacks of 50-50 Poxmix 50 A.M., 3/28/63. Bu	to 306'. Set 9-5/8" casing at 298' KB, r with 2% CaCl ₂ . Cement circulated. Plug ed 8-3/4" hole to 5724' KB. Set 7" casing KB, cemented through shoe with 11 sacks of and 25 sacks of regular with 2% CaCl ₂ . Plumped plug with 2000 psi, held okay. Cement Pozmix. Plug down at 2:05 P. M., 3/28/63.
emented we will at 1:30 to 5706' KB acel, 25 win at 10:10 to 50 to	3/63. Drilled 15" hole with 260 sacks of regular 0 A.M., 3/9/63. Drill 1, stage collar at 3960's sacks of 50-50 Poxmix 50 A.M., 3/28/63. But 110 sacks of 50-50 I g with 2000 psi, held of	to 306'. Set 9-5/8" casing at 298' KB, r with 2% CaCl ₂ . Cement circulated. Plug ed 8-3/4" hole to 5724' KB. Set 7" casing KB, cemented through shoe with 11 sacks of and 25 sacks of regular with 2% CaCl ₂ . Plumped plug with 2000 psi, held okay. Cement Pozmix. Plug down at 2:05 P. M., 3/28/63.
mented w wn at 1:30 5706' KB acel, 25 wn at 10: d stage w imped plu	3/63. Drilled 15" hole with 260 sacks of regular 0 A.M., 3/9/63. Drill 1, stage collar at 3960's sacks of 50-50 Poxmix 50 A.M., 3/28/63. But 110 sacks of 50-50 I g with 2000 psi, held of	to 306'. Set 9-5/8" casing at 298' KB, r with 2% CaCl ₂ . Cement circulated. Plug ed 8-3/4" hole to 5724' KB. Set 7" casing KB, cemented through shoe with 11 sacks of and 25 sacks of regular with 2% CaCl ₂ . Plumped plug with 2000 psi, held okay. Cement Pozmix. Plug down at 2:05 P. M., 3/28/63.
mented we will at 1:30 to 5706' KB acel, 25 win at 10:30 to stage will might be supported by the stage will be sta	3/63. Drilled 15" hole with 260 sacks of regular 0 A. M., 3/9/63. Drill 1, stage collar at 3960's sacks of 50-50 Poxmix 50 A. M., 3/28/63. But 110 sacks of 50-50 lag with 2000 psi, held of the plan of work must receive approve	to 306'. Set 9-5/8" casing at 298' KB, r with 2% CaCl ₂ . Cement circulated. Plug ed 8-3/4" hole to 5724' KB. Set 7" casing KB, cemented through shoe with 11 sacks of and 25 sacks of regular with 2% CaCl ₂ . Plug mped plug with 2000 psi, held okay. Cement Pozmix. Plug down at 2:05 P. M., 3/28/63. REFITCH SEP 1 9 1963 d in writing by the Geological Survey before our attions may be commenced. OIL CON. Color.
mented wwn at 1:30 5706' KB acel, 25 wn at 10: d stage wamped plu Iunderstand the	3/63. Drilled 15" hole with 260 sacks of regular 0 A. M., 3/9/63. Drill 1, stage collar at 3960' sacks of 50-50 Poxmix 50 A. M., 3/28/63. But 110 sacks of 50-50 I g with 2000 psi, held of the plan of work must receive approved the plan of work must receive approved Consolidated Sill & Gas	to 306'. Set 9-5/8" casing at 298' KB, r with 2% CaCl ₂ . Cement circulated. Plug ed 8-3/4" hole to 5724' KB. Set 7" casing KB, cemented through shoe with 11 sacks of and 25 sacks of regular with 2% CaCl ₂ . Plug mped plug with 2000 psi, held okay. Cement Pozmix. Plug down at 2:05 P. M., 3/28/63. REFITCH SEP 1 9 1963 d in writing by the Geological Survey before our attions may be commenced. OIL CON. Color.