

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY LP

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1700' FSL, 1650' FWL, Sec. 16, T-26-N, R-7-W, NMPM, Rio Arriba County

API # (assigned by OCD)

30-039-06464

5. Lease Number

6. State Oil & Gas Lease #

B-11183-51

7. Lease Name/Unit Name

Hamilton Com B

8. Well No.

4

9. Pool Name or Wildcat

~~Basin Fruitland Coal/~~
So Blanco Pict Cliffs

10. Elevation:

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

4-11-02 MIRU. SDON.

4-12-02 ND WH. NU BOP. PT BOP. TIH w/gauge ring to 2690'. TOOH. TIH w/5 1/2" CIBP, set @ 2685'. TOOH. TIH, tag CIBP @ 2685'. Load hole w/12 bbl wtr. Circ hole clean. PT 5 1/2" csg to 400 psi, failed. Establish injection into existing perfs. Plug #1: pump 110 sx Class "B" neat cmt inside csg @ 1714-2685' to cover Pictured Cliffs perfs, Fruitland, Kirtland & Ojo Alamo intervals. TOOH. SD for weekend.

4-15-02 (Henry Villeneuve, OCD on location). TIH, tag TOC @ 1680'. TOOH. TIH, perf 3 sqz holes @ 700'. Establish injection. TOOH. TIH w/5 1/2" cmt retainer, set @ 652'. PT 5 1/2" csg @ 0-652', failed. Establish injection. Plug #2: pump 43 sx Class "B" neat cmt w/2% calcium chloride below cmt retainer outside csg @ 600-700'. Pump 12 sx Class "B" neat cmt w/2% calcium chloride inside csg above cmt retainer inside csg @ 545-652'. TOOH. WOC. TIH, tag TOC @ 535'. TOOH. TIH, perf 3 sqz holes @ 183'. TOOH. Establish circ down csg & out bradenhead w/7 bbl wtr. Plug #3: pump 83 sx Class "B" neat cmt w/2% calcium chloride down csg & out bradenhead. Circ 0.5 bbl cmt to surface. WOC. ND BOP. Cut off WH. Found cmt down 25' in 9 5/8" annulus & down 20' in 5 1/2" csg. Fill 9 5/8" annulus & 5 1/2" csg w/20 sx Class "B" neat cmt. Install dry hole marker w/5 sx Class "B" neat cmt.

4-16-02 RD. Rig released.

Well plugged and abandoned 4-15-02.

SIGNATURE

[Signature]

Regulatory Supervisor May 13, 2002

no

(This space for State Use)

Approved by

ORIGINAL SIGNED BY E. VILLANUEVA

Title

Date

SEP 22 2002