'orm 9-331 b (April 1952)				Budget Bureau No. 42-R359.4. Approval expires 12-31-60.	
			 (SUBMIT IN TRIPLICATE)	Indian Agency	Jicarilla
٥			UNITED STATES	************	Apache
			 DEPARTMENT OF THE INTERIOR	Allottee	
	1		GEOLOGICAL SURVEY	F 57	116

SUNDRY NOTICES A	IND REPORTS ON WELLS						
ROYICE OF INVENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF X						
NOTICE OF INTENTION TO CHANGE PLANS	X SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING						
MOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING						
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.						
MOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT						
ROTICE OF INTENTION TO PULL OR ALTER CASING.	SUPPLEMENTARY WELL HISTORY.						
NOTICE OF INTENTION TO ABANDON WELL	Total TVIN						
(INDICATE ABOVE BY CHECK MARK	NATURE OF REPORT, NOTICE, OR OTHER DATA)						
fundada sa dina insula	MAR 20 1963						
	March 18 19 03 COM.						
Apache Well No. 2-16 is located 790 ft. fro	om $\begin{bmatrix} N \\ S \end{bmatrix}$ line and 1850 ft. from $\begin{bmatrix} N \\ W \end{bmatrix}$ line of sec. 16 DIST. 3						
NW 16 26N	3W NMPM (Meridian)						
Blanco Mesaverde Rio A							
(Field) (County Tapicito Pictured Cliffs	or Subdivision) (State or Territory)						
The elevation of the derrick floor above sea lev	vel is 7042, 6ft. KB						
INTERS A. I	LS OF WORK						
	the second of th						
ing points, and all o	es, weights, and lengths of proposed casings; indicate mudding jobs, dement-						
To complete as a Dictured Cliffs	Mesaverde dual completion - formerly						
	kota completion. Reason for change of						
plane is the inability to drill to 820	0' with gas due to heavy water production.						
plans is the mability to drill to 620	o with gas due to heavy water production.						
Drill to 330! Set 319! of 9-5/8" no	ine at 308 KB. Cement with 270 sy of						
Drill to 330'. Set 319' of 9-5/8" pipe at 308' KB. Cement with 270 sx. of regular cement, circulate cement. Drill to 3950'. Run 3956' of 7", 23 lb.							
casing, set at 3947' KB. Cement with 144 sx. regular cement. Drill to 6286'. Run 4-1/2", 10.5 lb. and 11.6 lb. casing as liner. Total of 2256'.							
	th 361 sx. 50/50 Pozmix cement with 4%						
	PC and MV effecting an approved type						
dual completion with packer separa	writing by the Geological Survey before operations may be commenced.						
	·						
Company Consolidated Oil & Ga	s, inc.						
Address 4150 East Mexico Avenue							
Denver 22, Colorado By William							
D	By Co ken Confer						
	Title Chief Engineer						