

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Tapacito Formation Pictured Cliffs County Rio Arriba
Initial X Annual - Special - Date of Test 12/13/57
Company Magnolia Petroleum Company Lease Jicarilla "C" Well No. 2 P.C.-UT
Unit N Sec. 7 Twp. 26N Rge. 3W Purchaser Pacific Northwest
Casing 7 5/8" Wt. 24# I.D. 7.025 Set at 3854 Perf. 3590 To 2641
Tubing 2 3/8" Wt. 4.7# I.D. 1.995 Set at 3550 Perf. - To -
Gas Pay: From 3590 To 3641 L 3550 xG est. 0.680 GL 2414 Bar. Press. est. 12 psi
Producing Thru: Casing - Tubing X Type Well dual completion
Single-Bradenhead-G. G. or G.O. Dual
Date of Completion: 10/4/57 Packer - Reservoir Temp. -

OBSERVED DATA

Tested Through (Pressure) (Choke) (Meter)Type Taps flange

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI										
1.	2"	0.750	97	-	57	856	57°	856	-	3 hrs.
2.						97		212	-	
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	12.865	-	109	1.0029	.9393	1.012	1285
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio - cf/bbl.Gravity of Liquid Hydrocarbons - deg.F_c - (1-e^{-s})Specific Gravity Separator Gas -Specific Gravity Flowing Fluid -P_c 868 P_c² 753

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w P _c
1.	224	-	-	-	-	50	703		
2.									
3.									
4.									
5.									

Absolute Potential: 1361 MCFPD; n 0.85COMPANY Magnolia Petroleum CompanyADDRESS Box 2106, Hobbs, New MexicoAGENT and TITLE William A. Morgan, Jr. Gas Engineer

WITNESSED

COMPANY -

REMARKS



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia
- P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if
flowing through casing.) psia
- P_f = Meter pressure, psia.
- h_w = Differential meter pressure, inches water.
- F_g = Gravity correction factor.
- F_t = Flowing temperature correction factor.
- F_{pv} = Supercompressability factor.
- n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .

OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
No. Copies Received <u>3</u>		
DISTRIBUTION		
	NO. FURNISHED	
Operator		
Santa Fe	1	
Proration Office		
State Land Office		
U. S. G. S.	1	
Transporter		
File	1	✓