Form 9-331 (April 1952)	To

## 11 X

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency
Apache
Allottee Contract #96
Loase No Jicsville "H"

SUNDRY NOTICES	AND	<b>REPORTS</b>	ON WELLS		[] []	F	I
----------------	-----	----------------	----------	--	----------	---	---

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	1 1	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	1 1	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
		SUBSEQUENT REPORT OF ABANDONMENT.
NOTICE OF INTENTION TO PULL OR ALTER CASING.		SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL.		
	.[	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

	?Pecent	<u> 97 19</u>	
Well No. 10 is locate	ed 1450 ft. from S line and	$\left\{\begin{array}{cc} 990 \text{ ft. from } \left\{\begin{array}{c} E \\ W \end{array}\right\} \text{ line} \right\}$	of PPHATO
58/4 Sec. 11	20N 3W	MPW	/RLULIVED /
(14 Sec. and Sec. No.)  Gevilan Pict. Cliffs	(Twp.) (Range) Rio Arriba	(Meridian)	DEC 27 1961
(Field)	(County or Subdivision)	New Mexico (State or Terri	OIL COIL COM.
The elevation of the derrick no	for above sea level is 106	t.	DIST. 3
	DETAILS OF WORL	r	

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

3747' TD, 3702' PBTD. 2-7/8" csg cstd & 3735' w/ 125 sx.

Perfd 3616/20, 3646/65, 3667/72, 3676/79, 3684/87 & 3639/94 w/ 2 jets/ft -sd-wtr frac w/ 41,000 gals, 14,000# 20/40 sd & 27,000# 10/20 sd in 3 stages
separated w/ 80 balls. BD 2500 psi, TP 3300 -- 2200 psi, IR 21 BPM,
instantaneous SIP -- vacuum.

Initial potential test (10/17/61) 3 hrs, 3/4" 495 Mcf/D, FCP 30 psig, CAOF 497
Mcf/D, STCP 763 psig/7days, Reperf'd 3616'/20, 3644/36, 3656/65, 3667/72,
3676/79 & 3684/86 w/ 2 jets/ft, Refrac w/ 45,000 gals 1% CaCl, wtr w/ 20#
J=98/1000 gal & 5000# walnut hulls in 3 stages separated w/ 2 batches of
500# of rock selt each. TP 2500 -- 2200 psi, IR 24 B/min,
Inst. SIP 100 psi. Prep retest.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Secony Mobil Oil Co., Inc.

P. O. Bex 3371

Address

Durango, Colorado

By PM Barry by PC Mulls

P. M. Barry

Titleist. Prod. Supt.

U.S. GOVERNMENT PRINTING OFFICE 18—8437b-8