Fori (A)	n 9-0 vil 19	31 <b>b</b> 52)	
	1	1	
		_	
			0

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Approv	al expires 12-31-60.
dian Agency	<u>Jicarilla</u>
Tr	ibal
llottee	
ase No	101

SUNDRY	NOTICES AND I	REPORTS ON WELLS	
	cupo	EQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO DRILL		EQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO CHANGE PI		EQUENT REPORT OF ALTERING CASING.	
NOTICE OF INTENTION TO TEST WATE		EQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO REDRILL O		EQUENT REPORT OF ABANDONMENT	
IOTICE OF INTENTION TO SHOOT OR		LEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO PULL OR A	1		
IOTICE OF INTENTION TO ABANDON	WELL		
(INDICAT	E ABOVE BY CHECK MARK NATURE OF	FREPORT, NOTICE, OR OTHER DATA)	•
		November 19	1963
Jicarilla C ell No. 1-11 is loc		ine and 990 ft. from E line of	f sec. <u>11</u>
E 11 (½ Sec. and Sec. No.)	26N 4W	NMPM (Xieridia)	
***	Rio Arriba	New Mexico	
Basin Dakota (Field)	(County or Subdivis	Anna Anna Anna Anna Anna Anna Anna Anna	<b>&gt;</b>
		858 KB WORK	
tate names of and expected depths to	DETAILS OF		ding jobs, cement-
Commenced drilling Drilled 6-1/4" hole to 5-1/2" casing on top, hrough casing shoe, at 5910' KB (Mesaver 18679' KB (Pictured Cheld okay.	DETAILS OF cobjective and s; show sizes, weighting points, and all other imposes 8008' KB, ran 249 set at 8005' KB, ce cemented with 88 sarde) and 98 sx. 50-5 sliffs). Bumped all p	WORK  s, and lengths of proposed casings; indicate mudreant proposed work)  old well - casing (7") set joints of 4-1/2" casing and emented with 106 sx. of 50 cs. 50-50 Diamix "A" through the poluge 10/20/63 with 2000 p	at 3539') d 1 joint of -50 Diamix gh stage co e collar at si - all plu
Commenced drilling orilled 6-1/4" hole to -1/2" casing on top, hrough casing shoe, t 5910' KB (Mesaver 679' KB (Pictured Collected okay.	DETAILS OF conjective sands; show sizes, weighting points, and all other imposes 8008' KB, ran 249 set at 8005' KB, concerned with 88 sande) and 98 sx. 50-5 liffs). Bumped all points and sand sand sand sand sand sand sand	WORK  s, and lengths of proposed casings; indicate mudrant proposed work)  old well - casing (7") set joints of 4-1/2" casing and emented with 106 sx. of 50 c. 50-50 Diamix "A" through the column of the color of t	at 3539') d 1 joint of -50 Diamix gh stage co e collar at si - all plu  REFERE  NOV 21 19
Commenced drilling Orilled 6-1/4" hole to 5-1/2" casing on top, hrough casing shoe, at 5910' KB (Mesaver 1679' KB (Pictured Coreld okay.  I understand that this plan of work company Conso.	DETAILS OF cobjective sands; show sizes, weighting points, and all other imposes to 8008' KB, ran 249 set at 8005' KB, cocemented with 88 strde) and 98 sx. 50-5 liffs). Bumped all published the same street was supposed in writing build a street was sup	WORK  s, and lengths of proposed casings; indicate mudrant proposed work)  old well - casing (7") set joints of 4-1/2" casing and emented with 106 sx. of 50 c. 50-50 Diamix "A" through the column of the color of t	at 3539') d 1 joint of -50 Diamix gh stage co e collar at si - all plu  REFIVE
Commenced drilling Drilled 6-1/4" hole to 5-1/2" casing on top, through casing shoe, at 5910' KB (Mesaver 18679' KB (Pictured Coneld okay.  I understand that this plan of work Company Conso.  Address 4150 East Me.	DETAILS OF cobjective sands; show sizes, weighting points, and all other imposes to 8008' KB, ran 249 set at 8005' KB, cocemented with 88 sorde) and 98 sx. 50-5 liffs). Bumped all published the same supposed in writing but have been supposed in	WORK  s, and lengths of proposed casings; indicate mudrant proposed work)  old well - casing (7") set joints of 4-1/2" casing and emented with 106 sx. of 50 c. 50-50 Diamix "A" through the column of the color of t	at 3539') d 1 joint of -50 Diamix gh stage co e collar at si - all plu  REFERE  NOV 21 19
Commenced drilling Drilled 6-1/4" hole to 5-1/2" casing on top, through casing shoe, at 5910' KB (Mesaver 18679' KB (Pictured Coneld okay.  I understand that this plan of work Company Conso	DETAILS OF cobjective sands; show sizes, weighting points, and all other imposes to 8008' KB, ran 249 set at 8005' KB, cocemented with 88 sorde) and 98 sx. 50-5 liffs). Bumped all published the same supposed in writing but have been supposed in	WORK  s, and lengths of proposed casings; indicate mudrant proposed work)  old well - casing (7") set joints of 4-1/2" casing and emented with 106 sx. of 50 c. 50-50 Diamix "A" through the column of the color of t	at 3539') d 1 joint of -50 Diamin gh stage co e collar at si - all plu  REFIVE  NOV 21 19 be commenced. OIL CON.