


ILLECIBLE



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office
Lease No.
Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

RECEIVED
MAY 14 1959

Well No. is located ft. from N line and ft. from E line of sec.
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

12-27-58 - run in well through perforation at 2216' to 2230', 2240' to 2250', and 2260' to 2280' with 10000 50-60 sand an 107,000 gallons water; fluidized with 14,500 gallons water. Perforation pressure 2200, reaction pressure 2200 to 2300. Prop 200 after 10,000 gallons, 50 after 20,000 gallons, 50 after 30,000 gallons, 50 after 40,000 gallons, 100 after 50,000 gallons and 100 after 60,000 gallons. Final pressure when pumps were stopped 1200, which did not increase. Treatment above to injection up a well. Now deliverability 1100-1200 per day.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company

Address

By

Title