U. S. GERLERIERL SURVEY

2

Jic. Apache Tribal

5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

| DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY | Contract #152 6. IF INDIAN, ALLOTTEE OR TRIBE NAME Apache |
|---|--|
| SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different eservoir, Use Form 9-331-C for such proposals.) | 8. FARM OR LEASE NAME |
| 1. oil gas X other | Jicarilla 152W 9. WELL NO. #1. (CMWO) |
| 2. NAME OF OPERATOR EL PASO NATURAL GAS CO. 3. ADDRESS OF OPERATOR BOX 990, FARMINGTON, NEW MEXICO 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 | #1 (OWWO) 10. FIELD OR WILDCAT NAME So. Blanco P.C Basin Dak. 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 7,T-26-N,R-5-W |
| below.) AT SURFACE: 800'S, 920'W AT TOP PROD. INTERVAL: AT TOTAL DEPTH: | 12. COUNTY OR PARISH 13. STATE Rio Arriba New Mexico 14. API NO. |
| 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA | 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6545' GL |
| REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING SUBSEQUENT REPORT OF: | (NOTE: Report results of multiple completion or zone change on Form 9–330.) |
| MULTIPLE COMPLETE | and the continue that dates |
| 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine 7/21/78: Pulled all tubing strings and packand squeezed w/150 sks cement. WOC. 7/23/78: Set cement retainer at 5137' and set cement retainer at 4742' and squeezed w/7/24/78: Drilled out retainer at 4742',5137,7460'. 7/26/78: Tripped in w/RTTS packer, pressure 7/28/78: PBTD 7480'. Perfed 7418-22 w/8 he w/60,000# 20/40 sand and 45,500 gal. gel war 7/29/78: Perfed 7316,7322,7350,7358,7378' was and and 32,000 gal. of gel water. Flushed | that to this work.)* ter. Set cement retainer at 7359' squeezed w/200 sks cement. WOC 200 sks cement. WOC. 7' and 7359' and cement to te tested to 4000#, OK. toles, 7442-64 w/20 holes. Fraced ter. Flushed w/2000 gal. water. w/1 SPZ. Fraced w/40,000# 20/40 |
| Subsurface Safety Valve: Manu. and Type | Set @ Ft. |
| 18. I hereby certify that the foregoing is true and correct SIGNED TITLE Drilling | 8/8/78 |
| (This space for Federal or the | DATE |
| APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY: | control 10 miles |
| *See Instructions on Revers | AUG 1 0 1973 |