

Form 9-331a  
(Feb. 1951)

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYLand Office Santa FeLease No. S.P. 079162

Unit \_\_\_\_\_

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<b>XX</b>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	DIST. <u>3</u>
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 9, 1952

Well No. M. H. L. 2-8 is located 1650 ft. from S line and 990 ft. from E line of sec. 7N. 1/2 Sec. 7  
(1/4 Sec. and Sec. No.)26 N  
(Twp.)7 N  
(Range)N.M.P.M.  
(Meridian)Wildcat  
(Field)San Arriba Co.  
(County or Subdivision)New Mexico  
(State or Territory)The elevation of the derrick floor above sea level is --- ft. (Will be furnished later)

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Proposed Pictured Cliffs sandstone well. Will set 150 ft. of 9 5/8" surface casing and circulate cement to surface. Will cement 5 1/2" casing on top of Pictured Cliffs sandstone at approx. 2125 ft. with 200 sacks of cement.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company KINGSLEY-LOCKE OIL CO.Address Luhra TowerPhoenix, ArizonaBy Frank C. BarnesTitle Geologist