

## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

## MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Undesignated Formation Pictured Cliffs County Rio Arriba  
Initial X Annual \_\_\_\_\_ Special \_\_\_\_\_ Date of Test 1-15-57  
Company Magnolia Petroleum Co. Lease Cheney-Federal Well No. 1  
Unit M Sec. 8 Twp. 26N Rge. 2W Purchaser \_\_\_\_\_  
Casing 7-5/8" Wt. 24# I.D. 7.025 Set at 3,980' Perf. 3,613' To 3,777' (4 sets)  
Tubing 2" Wt. 4.7# I.D. 1.995 Set at 3,614' Perf. \_\_\_\_\_ To \_\_\_\_\_  
Gas Pay: From 3,608' To 3,777' L 3,614' xG \_\_\_\_\_ -GL \_\_\_\_\_ Bar.Press. 12 psia  
Producing Thru: Casing \_\_\_\_\_ Tubing X Type Well G. G. Dual  
Single-Bradenhead-G. G. or G.O. Dual  
Date of Completion: 12-2-56 Packer No Reservoir Temp. \_\_\_\_\_

## OBSERVED DATA

Tested Through (Pressure) (Choke) (Velocity) Type Taps \_\_\_\_\_

No.	Flow Data			Tubing Data		Casing Data		Duration of Flow Hr.
	(Pressure) (Line) Size	(Choke) (Choke) Size	Press. psig	Diff. h <sub>w</sub>	Temp. °F.	Press. psig	Temp. °F.	
SI								
1.	2"	0.750"	Well flowed 64 minutes and died.					1 hr. 4 min.
2.								
3.								
4.								
5.								

## FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F <sub>t</sub>	Gravity Factor F <sub>g</sub>	Compress. Factor F <sub>pv</sub>	Rate of Flow Q-MCFPD @ 15.025 psia
1.							
2.							
3.							
4.							
5.							


## PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio \_\_\_\_\_ cf/bbl.  
Gravity of Liquid Hydrocarbons \_\_\_\_\_ deg.  
F<sub>c</sub> \_\_\_\_\_ (1-e<sup>-s</sup>)  
Specific Gravity Separator Gas \_\_\_\_\_  
Specific Gravity Flowing Fluid \_\_\_\_\_  
P<sub>c</sub> \_\_\_\_\_ P<sub>c</sub><sup>2</sup> \_\_\_\_\_

No.	P <sub>w</sub> P <sub>t</sub> (psia)	P <sub>c</sub> <sup>2</sup>	F <sub>c</sub> Q	(F <sub>c</sub> Q) <sup>2</sup> (1-e <sup>-s</sup> )	P <sub>w</sub> <sup>2</sup>	P <sub>c</sub> <sup>2</sup> -P <sub>w</sub> <sup>2</sup>	Cal. P <sub>w</sub>	P <sub>w</sub> P <sub>c</sub>
1.								
2.								
3.								
4.								
5.								

Absolute Potential: \_\_\_\_\_ MCFPD; n \_\_\_\_\_  
COMPANY Magnolia Petroleum Company  
ADDRESS P.O. Box 2406 - Hobbs, New Mexico  
AGENT and TITLE Walter H. King - Gas Engineer  
WITNESSED \_\_\_\_\_  
COMPANY \_\_\_\_\_

REMARKS



## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

$Q$  = Actual rate of flow at end of flow period at W. H. working pressure ( $P_w$ ).  
MCF/da. @ 15.025 psia and 60° F.

$P_c$  = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.  
psia

$P_w$  = Static wellhead working pressure as determined at the end of flow period.  
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

$P_t$  = Flowing wellhead pressure (tubing if flowing through tubing, casing if  
flowing through casing.) psia

$P_f$  = Meter pressure, psia.

$h_w$  = Differential meter pressure, inches water.

$F_g$  = Gravity correction factor.

$F_t$  = Flowing temperature correction factor.

$F_{pv}$  = Supercompressability factor.

$n$  = Slope of back pressure curve.

Note: If  $P_w$  cannot be taken because of manner of completion or condition of well, then  $P_w$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_t$ .

<b>OIL CONSERVATION COMMISSION</b>		
<b>AZTEC DISTRICT OFFICE</b>		
No. Copies Received		<b>84</b>
<b>DISTRIBUTION</b>		
	NO. COPIES	
Operator	/	
Santa Fe	/	
Proration Office	.	
State Land Office		
U. S. G. S.	/	
Transporter		
File	/	✓