	Fors (A)	n 9-1 pril 19	(2) (2) (2)	
1				
١	Ο,	. 8		
	•			
1				

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	and the second	 200%
	ma 18. G	
		6. s &
	可知為万學	
	Jicari	Har to
	and the second second	
	12	
Ar	acha	

71-41	hal Tas	
Allettes Tri	APT TA	-9-6
		- 12
	200	. •
Leade No.		

NOTICE OF INTENTION TO DRI	L	SUBSEQUENT REPORT OF WATER SHUT-OFF	-X	
NOTICE OF INTENTION TO CHA		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING SUBSEQUENT REPORT OF ALTERING CASHS SUBSEQUENT REPORT OF REDRILLING ON REPAIR SUBSEQUENT REPORT OF ARANDOMERT SUPPLEMENTARY WELL HISTORY		
NOTICE OF INTENTION TO TEXT				
NOTICE OF INTENTION TO SHO NOTICE OF INTENTION TO PULL				
NOTICE OF INTENTION TO ASA	•	SEP 1718		
	MONGATE ABOVE ST CHECK MAR	MINIONE OF THE OWNER OWNER OF THE OWNER OWN	GICAL SURVE	
		September 16	N, NEW MEXIC 1963	
Jicarilla				
ell No. 4-8	is located 1550 ft. f	rom N line and 890 ft. from N line of se	ــــــــــــــــــــــــــــــــــــــ	
NW/4 8_				
(14 See, and See, Me.)		(Manga) (Mathematical	OFTIAN	
Blanco Mesaverd Green Capicito Pictured	e Rio	ty or Subdivision) (State or Tempor)		
Capicito Pictured	i Ciiiis wick floor above sea l	level is 6958 ft. Ground Level	الما المال	
The electronic or one or		ALIS OF MORK	P191963	
	DELA	VITS OF MOKE	CON COI	
and account of any account do		alsoe, weights, and lengths of proposed easings; indicate healthy		
ate names of and expected de	pths to objective sender show ing points, and al	444. 4 44. 4. 14. 14. 14. 14. 14. 14. 14. 14. 1	DIST. 3	
er at 3631' KB, 0 psi at 6:00 A. I liner, pressure	e to 6127'. Set 4 cemented with 30 M. 7/13/63, held d to 1500 psi, did	1-1/2" casing as liner at 6126' KB, to 4 sacks of Diamix "A". Bumped plus okay. Cleaned out with 6-1/4" bit is not hold. Squeezed with 15 sacks or, pressured to 2700 psi, held okay.	op of ag with to top of regula;	
er at 3631' KB, 0 psi at 6:00 A. I liner, pressure	e to 6127'. Set 4 cemented with 30 M. 7/13/63, held d to 1500 psi, did	-1/2" casing as liner at 6126' KB, 14 sacks of Diamix "A". Bumped plu okay. Cleaned out with 6-1/4" bit inot hold. Squeezed with 15 sacks of	op of ag with to top of regula;	
er at 3631' KB, 0 psi at 6:00 A. I liner, pressure	e to 6127'. Set 4 cemented with 30 M. 7/13/63, held d to 1500 psi, did	-1/2" casing as liner at 6126' KB, 14 sacks of Diamix "A". Bumped plu okay. Cleaned out with 6-1/4" bit inot hold. Squeezed with 15 sacks of	op of ag with to top of regula;	
er at 3631' KB,) psi at 6:00 A. I liner, pressure	e to 6127'. Set 4 cemented with 30 M. 7/13/63, held d to 1500 psi, did	-1/2" casing as liner at 6126' KB, 14 sacks of Diamix "A". Bumped plu okay. Cleaned out with 6-1/4" bit inot hold. Squeezed with 15 sacks of	op of ag with to top of regula:	
er at 3631' KB, 0 psi at 6:00 A. I liner, pressured 23/63: Cleaned	e to 6127'. Set 4 cemented with 30 M. 7/13/63, held to 1500 psi, did out to top of line:	-1/2" casing as liner at 6126' KB, 14 sacks of Diamix "A". Bumped plu okay. Cleaned out with 6-1/4" bit inot hold. Squeezed with 15 sacks of	op of ag with to top of regula:	