

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Blanco Mesaverde Formation Mesaverde County Rio Arriba
Initial x Annual _____ Special _____ Date of Test 10/21/57
Company Magnolia Petroleum Company Lease Jicarilla "H" Well No. 3 MV L.T.
Unit 1 Sec. 12 Twp. 26N Rge. 3W Purchaser Pacific Northwest
Casing 5 1/2" Wt. 11.4 I.D. 5.012 Set at 6030 Perf. 5112 To 5654
Tubing 3/8" Wt. 4.7 I.D. 1.995 Set at 5118 Perf. - To -
Gas Pay: From 5112 To 5654 L 5118 xG .68(est) GL 3684 Bar.Press. 12
Producing Thru: Casing _____ Tubing x Type Well G.G. Dual
Date of Completion: 10/5/57 Packer Yes Reservoir Temp. _____
Single-Bradenhead-G. G. or G.O. Dual

OBSERVED DATA

Tested Through (Prover) (Choke) (Meter) Type Taps _____

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						1101				
1.	12"	0.75"	107	-	64	107	64	-	-	3 hr.
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_w P_f}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	12.365	-	119	.9962	.9393	-	3 hr.
2.							
3.							
4.							
5.							


PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
P_c 9.402 (1-e^{-s}) .235
Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid _____
P_c 1113 P_c² 1996.5

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w /P _c
1.	119	14.2	12.95	167.7	39.4	53.6	1942.2	231.5	.164
2.									
3.									
4.									
5.									

Absolute Potential: 1.405 MCFPD; n .75
COMPANY MAGNOLIA PETROLEUM COMPANY
ADDRESS BOX 2406, HOBBS, NEW MEXICO
AGENT and TITLE George J. Fowler, Gas Engineer
WITNESSED _____
COMPANY _____

REMARKS



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia
- P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if
flowing through casing.) psia
- P_f = Meter pressure, psia.
- h_w = Differential meter pressure, inches water.
- F_g = Gravity correction factor.
- F_t = Flowing temperature correction factor.
- F_{pv} = Supercompressability factor.
- n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .

OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
No. Copies Received		2
DISTRIBUTION		
	NO. FURNISHED	
Operator		
Santa Fe	1	
Production Office		
State Land Office		
U. S. G. S.	1	
Transporter		
File	1	2