STATE OF NEW MEXICO :NERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests In Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

perator		Caulkins	Oil Company	Lease	Breech "A	Α"	Well No.	175-E	
cation Well: I	Unit <u>B</u>	Sec. <u>8</u>	_Twp26 Nort	h Rge.	6 West	County	Rio Arr	iba	
NAME OF RESERVOIR OR POOL				TYPE OF PROD. M. (Oll or Gas)			D. MEDIUM J. or Cag.)		
Upper impletion									
Lower mpletion	÷	·•							
			PRE-FL	OW SHUT-IN P	RESSURE DATA				
Jpper Inpletion	Hour, date shut-in Length of time shut-in			ut-in	SI press, psig	Stab	Stabilized? (Yes or No)		
	Hour, date shut-in Length of time :		ut-in	SI press, psig		Stabilized? (Yes or No)			
				FLOW TEST	NO. 1				
nmenced	at (hour, dal	(e) * 5 -12 -8	35 7:45 AM		Zone producing (Up	per or Lower):			
TIM	IE	LAPSED TIME	PRES	SURE	PROD. ZONE	l			
(hour,		SINCE*	Upper Completion	Lower Completion	TEMP.	1	REMARKS		
5-13-		2/ "- "-	510	017					
7 :45 5 - 14 -		24 Hours	512	817		Both zone	s shut-in	<u>-</u>	
7:45 .		48 Hours	522	864		Both zone	s shut-in		
5-15-						Both Both	· ·		
7:45	АМ	72 Hours	523	864		Both zone	s shut-in	"	
-16-						Boen Botte	o birde III		
7:45		96 Hours	537	613		Dakota flo	owing - Me	sa Verde si	
5-17-									
7:45	AM	120 Hours	537	409		Dakota flo	owing - Me	sa Verde s	
 oductio	on rate d	uring test	<u></u>						
l:BOPD based on				Bbls. in	Hours	Grav.	G(OR	
15:			MCF	PD; Tested thru	(Orifice or Meter	:):	·		
	Valle Zara				RESSURE DATA				
Upper Length of time shut-in Length of tim					SI press, paig	Stab	ilized? (Yes or No)		
Lewer i	Hour, date s	nut-in	Length of time shi	ULIN	SI press, paig		And the same		
mpletion		· · · · · · · · · · · · · · · · · · ·				<u> U </u>	S O F :	· · ·	

OIL CON. DIV.

FLOW TEST NO. 2

PRESSURE

Zone producing (Upper or Lower):

1 IME	LAPSED TIME			PROD. ZONE		
(hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARKS	
•						
						
• .						
			-			
			·			
	 					
						
roduction rate d	neigo seco		<u> </u>		<u> </u>	
oduction face d	iming test	•		*****		
il:	BOPI	D based on	Bbls. in	Hours.	Grav GOR	
25:		MCF	PD: Tested thru	(Orifice or Meter	·):	
marks:						
						
hereby certify th	nat the informatio	on herein containe	ed is true and cor	nplete to the bes	t of my knowledge.	
	•	MAY 21 T	122		-	
	il Conservation D		₹4 9	perator	Caulkins Oil Company	
			R	1 John	eles Organ	
	Signed by CHARLE		D .	- Caroa	\mathcal{V}	
7			Т	tle	Superiotendent	
de DEPUTY O	L & GAS INSPECTO	R Dist at	_		5-20-85	
ue			D	ate	3-40-03	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commenced at (hour, date) **

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 3. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6 Fig. Test'No. 2 shall be conducted even in Fino leak was indicated during Flow 1 2.1 Presedure for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil of an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOP (oil zones only).