

COPY FOR  
STATE OF NEW MEXICO  
OIL CONSERVATION  
COMMISSION  
SUBMIT IN TRIPLICATE TO  
DISTRICT OFFICE

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office \_\_\_\_\_

Lease No. \_\_\_\_\_

Unit \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED  
DEC 27 1951  
OIL CON. COM.

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 1, 1951

Well No. 1 MBL is located 990 ft. from ☒ S line and 990 ft. from ☒ W line of sec. 5

SW Sec. 5  
(1/4 Sec. and Sec. No.)

26N 7W  
(Twp.) (Range)

N.M.P.M.  
(Meridian)

Wildcat  
(Field)

Rio Arriba  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 6033 ft. G.L.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate muddling jobs, cementing points, and all other important proposed work)

Well was shot as follows: 1400 qts. 4250-4599', 375 qts. 4100-4250', 275 qts. 3860-4100'. Well was shot open hole using solidified nitro-glycerin.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Kingsley-Locke Oil Co.

Address 1100 Lohrs Tower

Phoenix, Arizona

By \_\_\_\_\_

Title \_\_\_\_\_