

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other Shut In

2. NAME OF OPERATOR
DEPCO, Inc.

3. ADDRESS OF OPERATOR
1000 Petroleum Bldg - Denver, CO 80202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' FSL, 990' FWL (SW/4 SW/4)
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other)

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

NOV 24 1982

U. S. GEOLOGICAL SURVEY

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Permission to permanently abandon the MKL No. 1, which has been on a temporary abandoned status since November, 1966, is hereby requested.

Incomplete well records indicate the following pertinent information:

Surface Csg: 10-3/4" set @ 245' w/37 sx

Drld 8-3/4" hole to 3810'

Production Csg: 7" set @ 3810' w/100 sx

Open hole: 6 1/2" to 4534' TD

Liner: Indicated to be run, although no size or interval recorded in file

- O V E R -

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *[Signature]* TITLE Prod. Supt. - So. DATE November 22, 1982
Rockies

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

DEC 1 1982

U.S. GEOLOGICAL SURVEY

DIST. 3

NMOCC

*See Instructions on Reverse Side

DEC 1 1982

[Signature]
JAMES F. SIMS
DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-149

It is proposed to P&A this well in the following manner:

Zone	Log Top	Cmt Plug Ft3	Cmt Plug Interval
Cliff House	3790'	230	3690'-4534' TD
(Perforate 7" csg w/4 JS @ 3130')			
Chacra	3020'	90	2920'-3130'
(Perforate 7" csg w/4 JS @ 2180')			
Pict. Cliffs	2126'	65	2030'-2180'
(Perforate 7" csg w/4 JS @ 870')			
Ojo Alamo	820'	65	720'- 870'
(Perforate 7" csg w/4 JS @ 300')			
Base Surf Csg	245'	50	200'- 300'
Top Surf Csg		30	50'-Surf
Dry hole marker @ Surface			