



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 079162
Unit MKL

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent Report of Workover</u> x

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 31st, 19 57

Well No. 1-3 is located 990 ft. from S line and 990 ft. from E line of sec. 6

SE/4 SE/4 Sec. 6 26N 7W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

South Blanco PC Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6096 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casing; indicate casing jobs, cementing points, and all other important proposed work)

12-29-57 Moved in cable tools. Pulled tubing.

12-30-57 Sandfraced with 12,012 gallons water and 20,000# sand, flushed with 3,780 gallons water. Breakdown pressure 1000#, maximum treating pressure 1300#, minimum 1000#, average injection rate 49.8 barrels per minute.

12-31-57 After 12 hours flowing 1,054 MCF/day. Re-ran tubing.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company KING-LOC PETROLEUM COMPANY

Address 716 First National Bank Bldg.

Phoenix, Arizona

By George D. Locke

Title Secretary-Treasurer