

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Taurus Exploration, U.S.A., Inc.

3. Address and Telephone No.
2198 Bloomfield Highway; Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
990' FSL, 990' FWL, Sec. 1, T26N, R3W, NMPM

5. Lease Designation and Serial No.
Jicarilla 96

6. If Indian, Allottee or Tribe Name
Jicarilla

7. If Unit or CA, Agreement Designation

8. Well Name and No.
Jicarilla 96 #7

9. API Well No.
30-039-06659

10. Field and Pool, or exploratory Area
Gavilan PC/Blanco MV

11. County or Parish, State
Rio Arriba NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Add Pay & Commingle
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is intended to add the Upper Mesaverde/Lewis Shale and downhole commingle as follows:

- TOH and lay down PC tubing string.
- Release seal assembly and TOH.
- TIH with packer milling assembly. Mill out Baker Model "D" packer at 5390'. TOH.
- Set CIBP at 5350'. TIH with packer to 3800'. Test casing to 3000#. TOH.
- Run GR-CBL-CNL from 4100' - 5300'. Selectively perforated Mesaverde from 4210' - 5300'.
- TIH with packer to 4000'. Fracture Mesaverde with 70Q foam and sand.
- TOH with packer. TIH and clean out to 5920'. TOH.
- Run tubing set at 5850'. Install single wellhead.

Note: Top of Huerfanito Bentonite is 4135'.

An application to downhole commingle has been filed with the NMOCD.

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Superintendent

Date 7/2/98

(This space for Federal or State office use)

Approved by

Title

Lands and Mineral Resources

Date

AUG 10 1998

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side