

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Tapiçito Formation Pictured Cliffs County Rio Arriba
Initial X Annual _____ Special _____ Date of Test 9-19-56
Company Honolulu Oil Corporation Lease Jicarilla Well No. 4
Unit _____ Sec. 4 Twp. 26N Rge. 4-W Purchaser Southern Union Gas Co.
Casing 5 1/2 Wt. 114 I.D. _____ Set at 4031 Perf. 3945 To 3970
Tubing 2" Wt. 4.70 I.D. _____ Set at 3934 Perf. _____ To _____
Gas Pay: From 3945 To 3970 L _____ xG .710 -GL _____ Bar.Press. 124
Producing Thru: Casing _____ Tubing X Type Well Single
Single-Bradenhead-G. G. or G.O. Dual
Date of Completion: _____ Packer None Reservoir Temp. 110°

OBSERVED DATA

Tested Through (Braker) (Choke) (Meter) Type Taps _____

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Braker) (Line) Size	(Choke) (Braker) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						<u>1034</u>	<u>60</u>	<u>1034</u>	<u>60</u>	
1.	<u>2</u>	<u>1750</u>				<u>112</u>	<u>65</u>	<u>241</u>	<u>-</u>	<u>3 hours</u>
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_w p_f}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	<u>12.3650</u>		<u>112</u>	<u>.9952</u>	<u>.9193</u>	<u>1.014</u>	<u>1284.75</u>
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
F_c _____ (1-e^{-s})

Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid .710
P_c 1046 P_c² 1094

No.	P _w 241 (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w / P _c
1.	<u>241</u>					<u>58</u>	<u>1036</u>		
2.									
3.									
4.									
5.									

Absolute Potential: 1356 MCFPD; n .85

COMPANY Honolulu Oil Corporation
ADDRESS Braker 1391, Midland, Texas
AGENT and TITLE C. H. Evans, Division Gas Engineer
WITNESSED [Signature]
COMPANY Southern Union Gas Co.

REMARKS



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia
- P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if
flowing through casing.) psia
- P_f = Meter pressure, psia.
- h_w = Differential meter pressure, inches water.
- F_g = Gravity correction factor.
- F_t = Flowing temperature correction factor.
- F_{pv} = Supercompressability factor.
- n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .

OIL AND GAS COMMISSION		
SANTA FE OFFICE		
No. Copies Required <u>3</u>		
DISTRIBUTION		
	NO. FURNISHED	
Operator		
Santa Fe	/	
Production Office		
Geological Office		
Oil & Gas	/	
Transportation		
File	/	✓