

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	<input type="checkbox"/>
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL		<input type="checkbox"/>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 18, 1959

Well No. 6 is located 1450 ft. from SW line and 1450 ft. from W line of sec. 3

SW 1/4 Sec. 3 T-26N R-4W 100W
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Tapasito P.C. Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6914 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Casing - 8-5/8" at 282' - 235 sack cement - circulated
3-1/2" at 3810' - 300 sack cement
3-1/2" liner from 3737' to 6073' - 70 sack cement

Perforated 3-1/2" liner from 5540' to 5906'. Sandfrac with 60,000 gallons water and 60,000 lbs. sand. After recovery of sandfrac water well produced clean gas--no water.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Hessolulu Oil Corporation

Address Drawer 1391

Midland, Texas

By George R. Hoy

Title Division Development Engineer

