

APR 10 1953

STATE OF NEW MEXICO
OIL CONSERVATION COMMISSION
 DISTRICT NO. 3
 Phone 99 P. O. Box 697
 AZTEC, NEW MEXICO

(SUBMIT IN TRIPLICATE)

UNITED STATES
 DEPARTMENT OF THE INTERIOR
 GEOLOGICAL SURVEY

Land Office Santa Fe
 Lease No. 072302-AB
 Unit Rincon Unit
 I Sec. 916

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	☒	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 7, 1953

Well No. 3 is located 1265 ft. from N line and 1090 ft. from E line of sec. 6

SE 1/4 Sec. 6
 (1/4 Sec. and Sec. No.)

26N
 (Twp.)

6W
 (Range)

100W
 (Meridian)

Dorie Canyon
 (Field)

Rio Arriba
 (County or Subdivision)

New Mexico
 (State or Territory)

The elevation of the surface above sea level is 6592 ft. Ungraded ground

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drill 13 3/8 inch Rotary hole to 110 feet. Set 100 feet of 10 3/8 inch surface casing. Circulate cut with 100 sacks.

Drill 3 3/4 inch hole to 3100' or top of Pictured Cliff - set 20#, 7 inch casing with 100 sacks.

Drill 6 inch hole with Cable Tools from 3100 to 3200 feet.

Shoot open hole, tamped, with 300 quarts Nitro Gel.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Ralph A. Johnston

Address Box 313

Fortington, New Mexico

By James W. Copeland

Title Supt.

