(A)	oril 19	52)	

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

White or exputes 15-01-00.
Indian Agency Jicarilla
Apache
Allottee Socony-Mobil
Lease No. Contract 97

Budget Bureau No. 42-R359.4.

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY.
NOTICE OF INTENTION TO ABANDON WELL	1962
	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
UNDICATE ABOVE BY CHECK I	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  U. S. CIOLOGICAL SUNV
	August 7 62 62
Tribal "C"	<b>— .</b>
Well No. 4-6 is located 1190 ft	t. from $\begin{Bmatrix} \mathbf{N} \\ \mathbf{S} \end{Bmatrix}$ line and $\frac{820}{5}$ ft. from $\begin{Bmatrix} \mathbf{E} \\ \mathbf{W} \end{Bmatrix}$ line of sec. $\frac{6}{5}$
**	
SE 6 26N (34 Sec. and Sec. No.) (Twp.)	3W NMPM (Range) (Meridian)
Tapicito Pictured Cliffs Rio	
(Field) (O	ounty or Subdivision) (State or Territory)
	7127.
he elevation of the derrick floor above se	a level isit.
	· · · · · · · · · · · · · · · · · · ·
DE	TAILS OF WORK
DE	
DE	TAILS OF WORK
DE State names of and expected depths to objective sands; she ing points, and	CTAILS OF WORK  now sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- d all other important proposed work)
DE State names of and expected depths to objective sands; shing points, and	TAILS OF WORK  Now sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- d all other important proposed work)  Ran 3 5/8". 26.40# and 33.70# J-55 casing to
DE  State names of and expected depths to objective sands; shing points, and  Drilled 9 7/8" hole to 4150. F	CTAILS OF WORK  Tow sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- dell other important proposed work)  Ran 3 5/8". 26.40# and 33.70# J-55 casing to  cement, 45 sacks 40% Diasel followed by 195
DE  State names of and expected depths to objective sands; shing points, and  Drilled 9 7/8" hole to 4150. R  4041 cemented with 75 sacks sacks 50% Pozmix. Top of cem	TAILS OF WORK  Now sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- d all other important proposed work)  Ran 3 5/8". 26.40# and 33.70# J-55 casing to
DE  State names of and expected depths to objective sands; shing points, and  Drilled 9 7/8" hole to 4150. F	CTAILS OF WORK  Tow sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- dell other important proposed work)  Ran 3 5/8". 26.40# and 33.70# J-55 casing to  cement, 45 sacks 40% Diasel followed by 195
DE State names of and expected depths to objective sands; shing points, and  Drilled 9 7/8" hole to 4150. R  4041 cemented with 75 sacks sacks 50% Pozmix. Top of cem	CTAILS OF WORK  Tow sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- dell other important proposed work)  Ran 3 5/8". 26.40# and 33.70# J-55 casing to  cement, 45 sacks 40% Diasel followed by 195
DE State names of and expected depths to objective sands; shing points, and  Drilled 9 7/8" hole to 4150. R  4041 cemented with 75 sacks sacks 50% Pozmix. Top of cem	CTAILS OF WORK  Tow sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- dell other important proposed work)  Ran 3 5/8". 26.40# and 33.70# J-55 casing to  cement, 45 sacks 40% Diasel followed by 195
DE  State names of and expected depths to objective sands; shing points, and  Drilled 9 7/8" hole to 4150. R  4041 cemented with 75 sacks sacks 50% Pozmix. Top of cem	TAILS OF WORK  Town sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- d all other important proposed work)  Ran 3 5/8". 26.40# and 33.70# J-55 casing to cement, 45 sacks 40% Diasel followed by 195 ment 2750' by Temperature log. Tested casing
DE  State names of and expected depths to objective sands; shing points, and  Drilled 9 7/8" hole to 4150. R  4041 cemented with 75 sacks sacks 50% Pozmix. Top of cem	TAILS OF WORK  for sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- dail other important proposed work)  Ran 3 5/8". 26.40# and 33.70# J-55 casing to cement, 45 sacks 40% Diasel followed by 195 ment 2750' by Temperature log. Tested casing  AUG1 0 1962
DE  State names of and expected depths to objective sands; shing points, and  Drilled 9 7/8" hole to 4150. R  4041 cemented with 75 sacks sacks 50% Pozmix. Top of cem	TAILS OF WORK  Town sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- d all other important proposed work)  Ran 3 5/8". 26.40# and 33.70# J-55 casing to cement, 45 sacks 40% Diasel followed by 195 ment 2750' by Temperature log. Tested casing
DEState names of and expected depths to objective sands; shing points, and Drilled 9 7/8" hole to 4150'. F 4041' cemented with 75 sacks sacks 50% Pozmix. Top of cento 1500 psi - held O.K.	TAILS OF WORK  Tow sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- all other important proposed work)  Ran 3 5/8". 26.40# and 33.70# J-55 casing to cement, 45 sacks 40% Diasel followed by 195 ment 2750' by Temperature log. Tested casing  RECEIVED  AUG1 0 1962  CON. COM. DIST. 3
DEState names of and expected depths to objective sands; shing points, and Drilled 9 7/8" hole to 4150'. F 4041' cemented with 75 sacks sacks 50% Pozmix. Top of cento 1500 psi - held O.K.	TAILS OF WORK  Tow sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- and all other important proposed work)  Ran 3 5/8". 26.40# and 33.70# J-55 casing to cement, 45 sacks 40% Diasel followed by 195 ment 2750' by Temperature log. Tested casing  RECEIVED  AUG1 0 1962  CON. COM.
DE State names of and expected depths to objective sands; shing points, and Drilled 9 7/8" hole to 4150'. F 4041' cemented with 75 sacks sacks 50% Pozmix. Top of cem to 1500 psi - held O.K.	TAILS OF WORK  Tow sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- d all other important proposed work)  Ran 3 5/8". 26.40# and 33.70# J-55 casing to cement, 45 sacks 40% Diasel followed by 195 ment 2750' by Temperature log. Tested casing  RECEIVED  AUG1 0 1962  CON. COM. DIST. 3  oval in writing by the Geological Survey before operations may be commenced.
State names of and expected depths to objective sands; shing points, and Drilled 9 7/8" hole to 4150. F 4041 cemented with 75 sacks sacks 50% Pozmix. Top of cento 1500 psi - held O.K.	TAILS OF WORK  Tow sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- d all other important proposed work)  Ran 3 5/8". 26.40# and 33.70# J-55 casing to cement, 45 sacks 40% Diasel followed by 195 ment 2750' by Temperature log. Tested casing  RECEIVED  AUG1 0 1962  CON. COM. DIST. 3  oval in writing by the Geological Survey before operations may be commenced.
DE State names of and expected depths to objective sands; shing points, and Drilled 9 7/8" hole to 4150'. F 4041' cemented with 75 sacks sacks 50% Pozmix. Top of cent to 1500 psi - held O.K.  I understand that this plan of work must receive approaches Company Consolidated Oil & Gas, I	TAILS OF WORK  Tow sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- d all other important proposed work)  Ran 3 5/8". 26.40# and 33.70# J-55 casing to cement, 45 sacks 40% Diasel followed by 195 ment 2750' by Temperature log. Tested casing  RECEIVED  AUG1 0 1962  CON. COM. DIST. 3  oval in writing by the Geological Survey before operations may be commenced.
State names of and expected depths to objective sands; shing points, and Drilled 9 7/8" hole to 4150'. F 4041' cemented with 75 sacks sacks 50% Pozmix. Top of cem to 1500 psi - held O.K.	TAILS OF WORK  Tow sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- d all other important proposed work)  Ran 3 5/8". 26.40# and 33.70# J-55 casing to cement, 45 sacks 40% Diasel followed by 195 ment 2750' by Temperature log. Tested casing  RECEIVED  AUG1 0 1962  CON. COM. DIST. 3  oval in writing by the Geological Survey before operations may be commenced.